

Manual for Package PGFPLOTS_{TABLE}

Component of PGFPLOTS, Version 1.2.1

<http://sourceforge.net/projects/pgfplots>

Christian Feuersänger*
Institut für Numerische Simulation
Universität Bonn, Germany

February 12, 2009

Abstract

This package reads tab-separated numerical tables from input and generates code for pretty-printed \LaTeX -tabulars. It rounds to the desired precision and prints it in different number formatting styles.

Contents

1	Introduction	2
2	Loading and Displaying data	2
2.1	Text Table Input Format	2
2.2	Selecting Columns	5
2.3	Configuring Row Appearance	10
2.4	Customizing and Getting the Tabular Code	11
2.5	Defining Column Types for <code>tabular</code>	13
2.6	Number Formatting Options	14
2.6.1	Changing Number Format Display Styles	16
3	Fine Tuning of Loaded Data	19
3.1	Loading the table	20
3.2	Typesetting Cell Content	20
3.3	Preprocessing Cell Content	21
3.4	Postprocessing Cell Content	25
4	Generating Data in New Tables or Columns	26
4.1	Creating New Tables From Scratch	26
4.2	Creating New Columns From Existing Ones	27
4.3	Predefined Column Generation Methods	30
4.3.1	Acquiring Data Somewhere	30
4.3.2	Mathematical Operations	31
5	Miscellaneous	36
5.1	Writing (Modified) Tables To Disk	36
5.2	Miscellaneous Keys	36
5.3	Plain \TeX and Con \TeX t support	37
	Index	38

*<http://wissrech.ins.uni-bonn.de/people/feuersaenger>

1 Introduction

PGFPLOTS_{TABLE} is a lightweight sub-package of PGFPLOTS which employs its table input methods and the number formatting techniques to convert tab-separated tables into tabulars.

Its input is a text file containing space separated rows, possibly starting with column names. Its output is a L^AT_EX tabular¹ which contains selected columns of the text table, rounded to the desired precision, printed in the desired number format (fixed point, integer, scientific etc.).

It is used with

```
\usepackage{pgfplotstable}
% recommended:
%\usepackage{booktabs}
%\usepackage{array}
%\usepackage{colortbl}
```

and requires PGFPLOTS and PGF ≥ 2.00 installed.

`\pgfplotstableset{<key-value-options>}`

The user interface of this package is based on key-value-options. They determine what to display, how to format and what to compute.

Key-value pairs can be set in two ways:

1. As default settings for the complete document (or maybe a part of the document), using `\pgfplotstableset{<options>}`. For example, the document's preamble may contain

```
\pgfplotstableset{fixed zerofill,precision=3}
```

to configure a precision of 3 digits after the period, including zeros to get exactly 3 digits for all fixed point numbers.

2. As option which affects just a single table. This is provided as optional argument to the respective table typesetting command, for example `\pgfplotstabletypeset[<options>]{<file>}`.

Both ways are shown in the examples below.

Knowledge of `pgfkeys` is useful for a deeper insight into this package, as `.style`, `.append style` etc. are specific to `pgfkeys`. Please refer to the PGF manual, [1, section `pgfkeys`] if you want a deeper insight into `pgfkeys`. Otherwise, simply skip over to the examples provided in this document.

You will find key prefixes `/pgfplots/table/` and `/pgf/number format/`. These prefixes can be skipped if they are used in PGFPLOTS_{TABLE}; they belong to the “default key path” of `pgfkeys`.

2 Loading and Displaying data

2.1 Text Table Input Format

PGFPLOTS_{TABLE} works with plain text file tables in which entries (“cells”) are separated by a separation character. The initial separation character is “white space” which means “at least one space or tab” (see option `col sep` below). Those tables can have a header line which contains column names and most other columns typically contain numerical data.

The following listing shows `pgfplotstable.example1.dat` and is used often throughout this documentation.

```
# Convergence results
# fictional source, generated 2008
level  dof    error1      error2  info  grad(log(dof),log(error2))  quot(error1)
1      4      2.50000000e-01  7.57858283e-01  48    0                            0
2      16     6.25000000e-02  5.00000000e-01  25    -3.00000000e-01            4
3      64     1.56250000e-02  2.87174589e-01  41    -3.99999999e-01            4
4      256    3.90625000e-03  1.43587294e-01  8     -5.00000003e-01            4
5      1024   9.76562500e-04  4.41941738e-02  22    -8.49999999e-01            4
6      4096   2.44140625e-04  1.69802322e-02  46    -6.90000001e-01            4
7      16384  6.10351562e-05  8.20091159e-03  40    -5.24999999e-01            4
8      65536  1.52587891e-05  3.90625000e-03  48    -5.35000000e-01            3.99999999e+00
9      262144 3.81469727e-06  1.95312500e-03  33    -5.00000000e-01            4.00000001e+00
10     1048576 9.53674316e-07  9.76562500e-04  2     -5.00000000e-01            4.00000001e+00
```

¹Please see the remarks in section 5.3 for plain T_EX and ConT_EXt.

Lines starting with ‘%’ or ‘#’ are considered to be comment lines and are ignored.

There is future support for a second header line which must start with ‘\$flags ’ (the space is obligatory, even if the column separator is *not* space!). Currently, such a line is ignored. It may be used to provide number formatting options like precision and number format.

`\pgfplotstabletypeset` [*optional arguments*] {*file name or \macro*}

Loads (or acquires) a table and typesets it using the current configuration of number formats and table options.

In case the first argument is a file name, the table will be loaded from disk. Otherwise, it is assumed to be an already loaded table (see `\pgfplotstableread` or `\pgfplotstablenew`).

level	dof	error1	error2	info	grad(log(dof),log(error2))	quot(error1)
1	4	0.25	0.76	48	0	0
2	16	$6.25 \cdot 10^{-2}$	0.5	25	-0.3	4
3	64	$1.56 \cdot 10^{-2}$	0.29	41	-0.4	4
4	256	$3.91 \cdot 10^{-3}$	0.14	8	-0.5	4
5	1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	22	-0.85	4
6	4,096	$2.44 \cdot 10^{-4}$	$1.7 \cdot 10^{-2}$	46	-0.69	4
7	16,384	$6.1 \cdot 10^{-5}$	$8.2 \cdot 10^{-3}$	40	-0.52	4
8	65,536	$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	48	-0.54	4
9	$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	33	-0.5	4
10	$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	-0.5	4

`\pgfplotstabletypeset{pgfplotstable.example1.dat}`

The configuration can be customized with *optional arguments*. Configuration can be done for the complete table or for particular columns (or rows).

level	DOF	e_1	e_2	info	∇e_2	$\frac{e_1^{(n)}}{e_1^{(n-1)}}$
1	4	2.5^{-1}	$7.58 \cdot 10^{-1}$	+48.0	-	-
2	16	6.3^{-2}	$5.00 \cdot 10^{-1}$	+25.0	-0.3	4
3	64	1.6^{-2}	$2.87 \cdot 10^{-1}$	+41.0	-0.4	4
4	256	3.9^{-3}	$1.44 \cdot 10^{-1}$	+8.0	-0.5	4
5	1 024	9.8^{-4}	$4.42 \cdot 10^{-2}$	+22.0	-0.85	4
6	4 096	2.4^{-4}	$1.70 \cdot 10^{-2}$	+46.0	-0.69	4
7	16 384	6.1^{-5}	$8.20 \cdot 10^{-3}$	+40.0	-0.52	4
8	65 536	1.5^{-5}	$3.91 \cdot 10^{-3}$	+48.0	-0.54	4
9	262 144	3.8^{-6}	$1.95 \cdot 10^{-3}$	+33.0	-0.5	4
10	1 048 576	9.5^{-7}	$9.77 \cdot 10^{-4}$	+2.0	-0.5	4

```

\pgfplotstableset{% global config, for example in the preamble
  columns/dof/.style={int detect,column type=r,column name=\textsc{Dof}},
  columns/error1/.style={
    sci,sci zerofill,sci sep align,precision=1,sci superscript,
    column name=$e_1$,
  },
  columns/error2/.style={
    sci,sci zerofill,sci sep align,precision=2,sci 10e,
    column name=$e_2$,
  },
  columns/{grad(log(dof),log(error2))}/.style={
    string replace={0}{}, % erase '0'
    column name={\nabla e_2$},
    dec sep align,
  },
  columns/{quot(error1)}/.style={
    string replace={0}{}, % erase '0'
    column name={\frac{e_1^{(n)}}{e_1^{(n-1)}}}$}
  },
  empty cells with={--}, % replace empty cells with '--'
  every head row/.style={before row=\toprule,after row=\midrule},
  every last row/.style={after row=\bottomrule}
}
\pgfplotstabletypeset[ % local config, applies only for this table
  1000 sep={\,,},
  columns/info/.style={
    fixed,fixed zerofill,precision=1,showpos,
    column type=r,
  }
]
{pgfplotstable.example1.dat}

```

All of these options are explained in the following sections.

Technical note: every opened file will be protocollated into your log file.

`\pgfplotstabletypesetfile`[*{optional arguments}*]{*{file name}*}

Loads the table *{file name}* and typesets it. As of PGFPLOTS TABLE 1.2, this command is an alias to `\pgfplotstabletypeset`, that means the first argument can be either a file name or an already loaded table.

`\pgfplotstableread`{*{file name}*}{*{\macro}*}

Loads the table *{file name}* into a \TeX -macro *{\macro}*. This macro can then be used several times.

dof	error1	dof	error2
4	0.25	4	0.76
16	$6.25 \cdot 10^{-2}$	16	0.5
64	$1.56 \cdot 10^{-2}$	64	0.29
256	$3.91 \cdot 10^{-3}$	256	0.14
1,024	$9.77 \cdot 10^{-4}$	1,024	$4.42 \cdot 10^{-2}$
4,096	$2.44 \cdot 10^{-4}$	4,096	$1.7 \cdot 10^{-2}$
16,384	$6.1 \cdot 10^{-5}$	16,384	$8.2 \cdot 10^{-3}$
65,536	$1.53 \cdot 10^{-5}$	65,536	$3.91 \cdot 10^{-3}$
$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	$2.62 \cdot 10^5$	$1.95 \cdot 10^{-3}$
$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$1.05 \cdot 10^6$	$9.77 \cdot 10^{-4}$

```

\pgfplotstableread{pgfplotstable.example1.dat}\table
\pgfplotstabletypeset[columns={dof,error1}]\table
\hspace{2cm}
\pgfplotstabletypeset[columns={dof,error2}]\table

```

Technical note: every opened file will be protocollated into your log file.

`\pgfplotstablegetrowsof`{*{file name or \loadedtable}*}

Defines `\pgfmathresult` to be the number of rows in a table. The argument may be either a file name or an already loaded table (the *{\macro}* of `\pgfplotstableread`).

`/pgfplots/table/col sep=space|comma|semicolon|colon|braces` (initially space)

Specifies the column separation character for table reading. The initial choice, `space` means “at least one white space”. White spaces are tab stops or spaces (newlines always delimit lines).

For example, the file `pgfplotstable.example1.csv` uses commas as separation characters.

```
# Convergence results
# fictional source generated 2008
level,dof,error1,error2,info,{grad(log(dof),log(error2))},quot(error1)
1,9,2.50000000e-01,7.57858283e-01,48,0,0
2,25,6.25000000e-02,5.00000000e-01,25,-1.35691545e+00,4
3,81,1.56250000e-02,2.87174589e-01,41,-1.17924958e+00,4
4,289,3.90625000e-03,1.43587294e-01,8,-1.08987331e+00,4
5,1089,9.76562500e-04,4.41941738e-02,22,-1.04500712e+00,4
6,4225,2.44140625e-04,1.69802322e-02,46,-1.02252239e+00,4
7,16641,6.10351562e-05,8.20091159e-03,40,-1.01126607e+00,4
8,66049,1.52587891e-05,3.90625000e-03,48,-1.00563427e+00,3.99999999e+00
9,263169,3.81469727e-06,1.95312500e-03,33,-1.00281745e+00,4.00000001e+00
10,1050625,9.53674316e-07,9.76562500e-04,2,-1.00140880e+00,4.00000001e+00
```

Thus, we need to specify `col sep=comma` when we read it.

level	dof	error1	error2	info	grad(log(dof),log(error2))	quot(error1)
1	4	0.25	0.76	48	0	0
2	16	$6.25 \cdot 10^{-2}$	0.5	25	-0.3	4
3	64	$1.56 \cdot 10^{-2}$	0.29	41	-0.4	4
4	256	$3.91 \cdot 10^{-3}$	0.14	8	-0.5	4
5	1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	22	-0.85	4
6	4,096	$2.44 \cdot 10^{-4}$	$1.7 \cdot 10^{-2}$	46	-0.69	4
7	16,384	$6.1 \cdot 10^{-5}$	$8.2 \cdot 10^{-3}$	40	-0.52	4
8	65,536	$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	48	-0.54	4
9	$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	33	-0.5	4
10	$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	-0.5	4

```
\pgfplotstabletypeset[col sep=comma]{pgfplotstable.example1.csv}
```

You may call `\pgfplotstableset{col sep=comma}` once in your preamble if all your tables use commas as column separator.

Please note that if cell entries (for example column names) contain the separation character, you need to enclose the column entry in *braces*: `{grad(log(dof),log(error2))}`. If you want to use unmatched braces, you need to write a backslash before the brace. For example the name ‘`column{withbrace}`’ needs to be written as ‘`column\{withbrace}`’.

Furthermore, if you need empty cells in case `col sep=space`, you have to provide `{}` to delimit such a cell since `col sep=space` uses *at least* one white space (consuming all following ones).

The value `col sep=braces` is special since it actually uses two separation characters. Every single cell entry is delimited by an opening and a closing brace, `{(entry)}`, for this choice. Furthermore, any white spaces (spaces and tabs) between cell entries are *skipped* in case `braces` until the next `{(entry)}` is found.

`/pgfplots/table/header={boolean}` (initially true)

Configures if column names shall be identified during input operations.

The ‘header’ is the first non-comment line, but only if this line contains non-numerical entries. If the first non-comment line contains at least one non-numerical entry (for example ‘`a name`’), each entry in this line is supposed to be a column name.

If the first non-comment line contains only numerical data, it is used as data row. In this case, column indices will be assigned as column “names”.

Use `header=false` to force this last case, i.e. even if the first line contains strings, they won’t be recognised as column names.

2.2 Selecting Columns

`/pgfplots/table/columns={comma-separated-list}`

Selects particular columns the table. If this option is empty (has not been provided), all available columns will be selected.

Inside of $\{\langle\text{comma-separated-list}\rangle\}$, column names as they appear in the table’s header are expected. If there is no header, simply use column indices. If there are column names, the special syntax $[\text{index}]\langle\text{integer}\rangle$ can be used to select columns by index. The first column has index 0.

dof	level	info
4	1	48
16	2	25
64	3	41
256	4	8
1,024	5	22
4,096	6	46
16,384	7	40
65,536	8	48
$2.62 \cdot 10^5$	9	33
$1.05 \cdot 10^6$	10	2

```
\pgfplotstabletypeset[columns={dof,level,[index]4}]{pgfplotstable.example1.dat}
```

```
/pgfplots/table/alias/<col name>/.initial={<real col name>}
```

Assigns the new name $\langle\text{new col name}\rangle$ for the column denoted by $\langle\text{real col name}\rangle$. Afterwards, accessing $\langle\text{new col name}\rangle$ will use the data associated with column $\langle\text{real col name}\rangle$.

You can use `columns/<new col name>/.style` to assign styles for the alias, not for the original column name.

If there exists both an alias and a column of the same name, the column name will be preferred. Furthermore, if there exists a `create on use` statement with the same name, this one will also be preferred.

In case $\langle\text{new col name}\rangle$ contains characters which are required for key settings, you need to use braces around it: `alias/{name=wi/th,special}/.initial={othername}`.

```
/pgfplots/table/columns/<column name>/.style={<key-value-list>}
```

Sets all options in $\{\langle\text{key-value-list}\rangle\}$ exclusively for $\{\langle\text{column name}\rangle\}$.

level	DOF	L_2	A	info	$\text{grad}(\log(\text{dof}),\log(\text{error2}))$	$\text{quot}(\text{error1})$
1	4	2.500_{-1}	7.58_{-1}	48	0	0
2	16	6.250_{-2}	5.00_{-1}	25	-0.3	4
3	64	1.563_{-2}	2.87_{-1}	41	-0.4	4
4	256	3.906_{-3}	1.44_{-1}	8	-0.5	4
5	1,024	9.766_{-4}	4.42_{-2}	22	-0.85	4
6	4,096	2.441_{-4}	1.70_{-2}	46	-0.69	4
7	16,384	6.104_{-5}	8.20_{-3}	40	-0.52	4
8	65,536	1.526_{-5}	3.91_{-3}	48	-0.54	4
9	262,144	3.815_{-6}	1.95_{-3}	33	-0.5	4
10	1,048,576	9.537_{-7}	9.77_{-4}	2	-0.5	4

```
\pgfplotstabletypeset[
  columns/error1/.style={
    column name=$L_2$,
    sci,sci zerofill,sci subscript,
    precision=3},
  columns/error2/.style={
    column name=$A$,
    sci,sci zerofill,sci subscript,
    precision=2},
  columns/dof/.style={
    int detect,
    column name=\textsc{Dof}
  }
]
{pgfplotstable.example1.dat}
```

If your column name contains commas ‘,’ , slashes ‘/’ or equal signs ‘=’ , you need to enclose the column name in braces.

DOF	L_2	slopes L_2
4	2.500 ₋₁	0.0
16	6.250 ₋₂	-0.3
64	1.563 ₋₂	-0.4
256	3.906 ₋₃	-0.5
1,024	9.766 ₋₄	-0.8
4,096	2.441 ₋₄	-0.7
16,384	6.104 ₋₅	-0.5
65,536	1.526 ₋₅	-0.5
262,144	3.815 ₋₆	-0.5
1,048,576	9.537 ₋₇	-0.5

```
\pgfplotstabletypeset[
  columns={dof,error1,{grad(log(dof),log(error2))}},
  columns/error1/.style={
    column name=$L_2$,
    sci,sci zerofill,sci subscript,
    precision=3},
  columns/dof/.style={
    int detect,
    column name=\textsc{Dof}},
  columns/{grad(log(dof),log(error2))}/.style={
    column name=slopes $L_2$,
    fixed,fixed zerofill,
    precision=1}
]
{pgfplotstable.example1.dat}
```

If your tables don’t have column names, you can simply use integer indices instead of $\{ \langle column\ name \rangle \}$ to refer to columns. If you have column names, you can’t set column styles using indices.

`/pgfplots/table/display columns/⟨index⟩/.style={⟨key-value-list⟩}`

Applies all options in $\{ \langle key-value-list \rangle \}$ exclusively to the column which will appear at position $\langle index \rangle$ in the output table.

In contrast to the `table/columns/⟨name⟩` styles, this option refers to the output table instead of the input table. Since the output table has no unique column name, you can only access columns by index.

Indexing starts with $\langle index \rangle = 0$.

Display column styles override input column styles.

`/pgfplots/table/every col no ⟨index⟩` (style, no value)

A style which is identical with `display columns/⟨index⟩`: it applies exclusively to the column at position $\langle index \rangle$ in the output table.

See `display columns/⟨index⟩` for details.

`/pgfplots/table/column type={⟨tabular column type⟩}` (initially c)

Contains the column type for `tabular`.

If all column types are empty, the complete argument is skipped (assuming that no `tabular` environment is generated).

Use `\pgfplotstableset{column type/.add={⟨before⟩}{⟨after⟩}}` to *modify* a value instead of overwriting it. The `.add` key handler works for other options as well.

dof	error1	info
4	0.25	48
16	$6.25 \cdot 10^{-2}$	25
64	$1.56 \cdot 10^{-2}$	41
256	$3.91 \cdot 10^{-3}$	8
1,024	$9.77 \cdot 10^{-4}$	22
4,096	$2.44 \cdot 10^{-4}$	46
16,384	$6.1 \cdot 10^{-5}$	40
65,536	$1.53 \cdot 10^{-5}$	48
$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	33
$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	2

```
\pgfplotstabletypeset[
  columns={dof,error1,info},
  column type/.add={|}{% results in '|c'
}
{pgfplotstable.example1.dat}
```

`/pgfplots/table/assign column name/.code={⟨...⟩}`

Allows to *modify* the value of `column name`.

Argument #1 is the current column name, that means after evaluation of `column name`. After `assign column name`, a new (possibly modified) value for `column name` should be set.

That means you can use `column name` to assign the name as such and `assign column name` to generate final T_EX code (for example to insert `\multicolumn{1}{c}{#1}`).

Default is empty which means no change.

`/pgfplots/table/multicolumn names={\tabular column type}` (style, initially c)

A style which typesets each column name using a `\multicolumn{1}{\tabular column type}{the column name}` statement.

`/pgfplots/table/dec sep align={\header column type}` (style, initially c)

A style which aligns numerical columns at the decimal separator.

The first argument determines the alignment of the header column.

The style `dec sep align` actually introduces two new `\tabular` columns², namely `r@{}`. It introduces multicolumns for column names accordingly and handles numbers which do not have a decimal separator.

Please note that you need `\usepackage{array}` for this style.

dof	error1	error2	info	grad(log(dof),log(error2))
4	0.25	7.58 ₋₁	48	0
16	6.25 · 10 ⁻²	5.00 ₋₁	25	-0.3
64	1.56 · 10 ⁻²	2.87 ₋₁	41	-0.4
256	3.91 · 10 ⁻³	1.44 ₋₁	8	-0.5
1,024	9.77 · 10 ⁻⁴	4.42 ₋₂	22	-0.85
4,096	2.44 · 10 ⁻⁴	1.70 ₋₂	46	-0.69
16,384	6.1 · 10 ⁻⁵	8.20 ₋₃	40	-0.52
65,536	1.53 · 10 ⁻⁵	3.91 ₋₃	48	-0.54
2.62 · 10 ⁵	3.81 · 10 ⁻⁶	1.95 ₋₃	33	-0.5
1.05 · 10 ⁶	9.54 · 10 ⁻⁷	9.77 ₋₄	2	-0.5

```
% requires \usepackage{array}
\pgfplotstabletypeset[
  columns={dof,error1,error2,info,{grad(log(dof),log(error2))}},
  columns/error1/.style={dec sep align},
  columns/error2/.style={sci,sci subscript,sci zerofill,dec sep align},
  columns/info/.style={fixed,dec sep align},
  columns/{grad(log(dof),log(error2))}/.style={fixed,dec sep align}
]
{pgfplotstable.example1.dat}
```

Or with comma as decimal separator:

dof	error1	error2	info	grad(log(dof),log(error2))
4	0,25	7,58 ₋₁	48	0
16	6,25 · 10 ⁻²	5,00 ₋₁	25	-0,3
64	1,56 · 10 ⁻²	2,87 ₋₁	41	-0,4
256	3,91 · 10 ⁻³	1,44 ₋₁	8	-0,5
1.024	9,77 · 10 ⁻⁴	4,42 ₋₂	22	-0,85
4.096	2,44 · 10 ⁻⁴	1,70 ₋₂	46	-0,69
16.384	6,1 · 10 ⁻⁵	8,20 ₋₃	40	-0,52
65.536	1,53 · 10 ⁻⁵	3,91 ₋₃	48	-0,54
2,62 · 10 ⁵	3,81 · 10 ⁻⁶	1,95 ₋₃	33	-0,5
1,05 · 10 ⁶	9,54 · 10 ⁻⁷	9,77 ₋₄	2	-0,5

```
% requires \usepackage{array}
\pgfplotstabletypeset[
  use comma,
  columns={dof,error1,error2,info,{grad(log(dof),log(error2))}},
  columns/error1/.style={dec sep align},
  columns/error2/.style={sci,sci subscript,sci zerofill,dec sep align},
  columns/info/.style={fixed,dec sep align},
  columns/{grad(log(dof),log(error2))}/.style={fixed,dec sep align}
]
{pgfplotstable.example1.dat}
```

It may be advisable to use the `zerofill` variants to force at least one digit after the decimal separator.

²Unfortunately, `dec sep align` is currently not very flexible when it comes to column type modifications. In particular, it is not possible to use colored columns or cells in conjunction with `dec sep align`. The `\rowcolor` command works properly; the color hangover introduced by `colortbl` is adjusted automatically.

Please note that this style overwrites `column type`, `assign cell content` and some number formatting settings.

`/pgfplots/table/sci sep align={\langle header column type \rangle}` (style, initially c)

A style which aligns numerical columns at the exponent in scientific representation.

The first argument determines the alignment of the header column.

It works similarly to `dec sep align`, namely by introducing two artificial columns `r@{1}` for alignment.

Please note that you need `\usepackage{array}` for this style.

Please note that this style overwrites `column type`, `assign cell content` and some number formatting settings.

`/pgfplots/table/dcolumn={\langle tabular column type \rangle}{\langle type for column name \rangle}` (style, initially `{D{.}{.}{2}}{c}`)

A style which can be used together with the `dcolumn` package of David Carlisle. It also enables alignment at the decimal separator. However, the decimal separator needs to be exactly one character which is incompatible with ‘{,}’ (the default setting for `use comma`).

`/pgfplots/table/every first column` (style, no value)

A style which is installed for every first column only.

level	dof	error1	error2	info	grad(log(dof),log(error2))	quot(error1)
1	4	0.25	0.76	48	0	0
2	16	$6.25 \cdot 10^{-2}$	0.5	25	-0.3	4
3	64	$1.56 \cdot 10^{-2}$	0.29	41	-0.4	4
4	256	$3.91 \cdot 10^{-3}$	0.14	8	-0.5	4
5	1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	22	-0.85	4
6	4,096	$2.44 \cdot 10^{-4}$	$1.7 \cdot 10^{-2}$	46	-0.69	4
7	16,384	$6.1 \cdot 10^{-5}$	$8.2 \cdot 10^{-3}$	40	-0.52	4
8	65,536	$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	48	-0.54	4
9	$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	33	-0.5	4
10	$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	-0.5	4

```
\pgfplotstabletypeset[
every head row/.style={before row=\hline,after row=\hline\hline},
every last row/.style={after row=\hline},
every first column/.style={
column type/.add={|}{}}
},
every last column/.style={
column type/.add={|}{}}
]]
{pgfplotstable.example1.dat}
```

`/pgfplots/table/every last column` (style, no value)

A style which is installed for every last column only.

`/pgfplots/table/every even column` (style, no value)

A style which is installed for every column with even column index (starting with 0).

```
\pgfplotstableset{
columns={dof,error1,{grad(log(dof),log(error2))},info},
columns/error1/.style={
column name=$L_2$,
sci,sci zerofill,sci subscript,
precision=3},
columns/dof/.style={
int detect,
column name=\textsc{Dof}},
columns/{grad(log(dof),log(error2))}/.style={
column name=slopes $L_2$,
fixed,fixed zerofill,
precision=1}}
```

Dof	L_2	slopes L_2	info
4	2.500 ₋₁	0.0	48
16	6.250 ₋₂	-0.3	25
64	1.563 ₋₂	-0.4	41
256	3.906 ₋₃	-0.5	8
1,024	9.766 ₋₄	-0.8	22
4,096	2.441 ₋₄	-0.7	46
16,384	6.104 ₋₅	-0.5	40
65,536	1.526 ₋₅	-0.5	48
262,144	3.815 ₋₆	-0.5	33
1,048,576	9.537 ₋₇	-0.5	2

```
% requires \usepackage{colortbl}
\pgfplotstabletypeset[
  every even column/.style={
    column type/.add={>{\columncolor[gray]{.8}}}{}}{}
]
{pgfplotstable.example1.dat}
```

`/pgfplots/table/every odd column` (style, no value)

A style which is installed for every column with odd column index (starting with 0).

`\pgfplotstablecol`

During the evaluation of row or column options, this command expands to the current columns' index.

`\pgfplotstablerow`

During the evaluation of row or column options, this command expands to the current rows' index.

`\pgfplotstablecols`

During the evaluation of row or column options, this command expands to the total number of columns in the output table.

`\pgfplotstablerows`

During evaluation of *columns*, this command expands to the total number of *input* rows. You can use it inside of row predicate.

During evaluation of *rows*, this command expands to the total number of *output* rows.

2.3 Configuring Row Appearance

The following styles allow to configure the final table code *after any cell contents have been assigned*.

`/pgfplots/table/before row={\TeX code}`

Contains \TeX code which will be installed before the first cell in a row.

`/pgfplots/table/after row={\TeX code}`

Contains \TeX code which will be installed after the last cell in a row (i.e. after $\backslash\backslash$).

`/pgfplots/table/every even row` (style, no value)

A style which is installed for each row with even row index. The first row is supposed to be a "head" row and does not count. Indexing starts with 0.

```
\pgfplotstableset{
  columns={dof,error1,{grad(log(dof),log(error2))}},
  columns/error1/.style={
    column name=$L_2$,
    sci,sci zerofill,sci subscript,
    precision=3},
  columns/dof/.style={
    int detect,
    column name=\textsc{Dof}},
  columns/{grad(log(dof),log(error2))}/.style={
    column name=slopes $L_2$,
    fixed,fixed zerofill,
    precision=1}}
```

DOF	L_2	slopes L_2
4	2.500 ₋₁	0.0
16	6.250 ₋₂	-0.3
64	1.563 ₋₂	-0.4
256	3.906 ₋₃	-0.5
1,024	9.766 ₋₄	-0.8
4,096	2.441 ₋₄	-0.7
16,384	6.104 ₋₅	-0.5
65,536	1.526 ₋₅	-0.5
262,144	3.815 ₋₆	-0.5
1,048,576	9.537 ₋₇	-0.5

```
% requires \usepackage{booktabs}
\pgfplotstablotypeset[
  every head row/.style={
    before row=\toprule,after row=\midrule},
  every last row/.style={
    after row=\bottomrule},
]
{pgfplotstable.example1.dat}
```

DOF	L_2	slopes L_2
4	2.500 ₋₁	0.0
16	6.250 ₋₂	-0.3
64	1.563 ₋₂	-0.4
256	3.906 ₋₃	-0.5
1,024	9.766 ₋₄	-0.8
4,096	2.441 ₋₄	-0.7
16,384	6.104 ₋₅	-0.5
65,536	1.526 ₋₅	-0.5
262,144	3.815 ₋₆	-0.5
1,048,576	9.537 ₋₇	-0.5

```
% requires \usepackage{booktabs,colortbl}
\pgfplotstablotypeset[
  every even row/.style={
    before row={\rowcolor[gray]{0.9}}},
  every head row/.style={
    before row=\toprule,after row=\midrule},
  every last row/.style={
    after row=\bottomrule},
]
{pgfplotstable.example1.dat}
```

`/pgfplots/table/every odd row` (style, no value)

A style which is installed for each row with odd row index. The first row is supposed to be a “head” row and does not count. Indexing starts with 0.

`/pgfplots/table/every head row` (style, no value)

A style which is installed for each first row in the tabular. This can be used to adjust options for column names or to add extra lines/colours.

`/pgfplots/table/every first row` (style, no value)

A style which is installed for each first *data* row, i.e. after the head row.

`/pgfplots/table/every last row` (style, no value)

A style which is installed for each last *data* row.

`/pgfplots/table/every row no $\langle index \rangle$` (style, no value)

A style which is installed for the row with index $\langle index \rangle$.

2.4 Customizing and Getting the Tabular Code

`/pgfplots/table/every table= $\{\langle file name \rangle\}$`

A style which is installed at the beginning of every `\pgfplotstablotypeset` command.

The table file name is given as first argument.

`/pgfplots/table/font= $\{\langle font name \rangle\}$` (initially empty)

Assigns a font used for the complete table.

`/pgfplots/table/begin table= $\{\langle code \rangle\}$` (initially `\begin{tabular}`)

Contains $\{\langle code \rangle\}$ which is generated as table start.

`/pgfplots/table/typeset cell/.code= $\{\langle \dots \rangle\}$`

A code key which assigns `/pgfplots/table/@cell` content to the final output of the current cell.

The first argument, #1, is the final cell's value. After this macro, the value of @cell content will be written to the output.

The default implementation is

```
\ifnum\pgfplotstablecol=\pgfplotstablecols
  \pgfkeyssetvalue{/pgfplots/table/cell content}{#1\}%
\else
  \pgfkeyssetvalue{/pgfplots/table/cell content}{#1&}\%
\fi
```

Attention: The value of `\pgfplotstablecol` is now in the range $1, \dots, n$ where $n = \text{\pgfplotstablecols}$. This simplifies checks whether we have the last column.

`/pgfplots/table/end table={code}` (initially `\end{tabular}`)

Contains `{code}` which is generated as table end.

`/pgfplots/table/outfile={file name}` (initially empty)

Writes the generated tabular code into `{file name}`. It can then be used with `\input{file name}`, `PGFPLOTSTABLE` is no longer required since it contains a completely normal `tabular`.

dof	error1
4	0.25
16	$6.25 \cdot 10^{-2}$
64	$1.56 \cdot 10^{-2}$
256	$3.91 \cdot 10^{-3}$
1,024	$9.77 \cdot 10^{-4}$
4,096	$2.44 \cdot 10^{-4}$
16,384	$6.1 \cdot 10^{-5}$
65,536	$1.53 \cdot 10^{-5}$
$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$
$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$

```
\pgfplotstabletypeset[
  columns={dof,error1},
  outfile=pgfplotstable.example1.out.tex]
{pgfplotstable.example1.dat}
```

and `pgfplotstable.example1.out.tex` contains

```
\begin {tabular}{cc}%
dof&error1\\%
\pgfutilensurermath {4}&\pgfutilensurermath {0.25}\\%
\pgfutilensurermath {16}&\pgfutilensurermath {6.25\cdot 10^{-2}}\\%
\pgfutilensurermath {64}&\pgfutilensurermath {1.56\cdot 10^{-2}}\\%
\pgfutilensurermath {256}&\pgfutilensurermath {3.91\cdot 10^{-3}}\\%
\pgfutilensurermath {1{,}024}&\pgfutilensurermath {9.77\cdot 10^{-4}}\\%
\pgfutilensurermath {4{,}096}&\pgfutilensurermath {2.44\cdot 10^{-4}}\\%
\pgfutilensurermath {16{,}384}&\pgfutilensurermath {6.1\cdot 10^{-5}}\\%
\pgfutilensurermath {65{,}536}&\pgfutilensurermath {1.53\cdot 10^{-5}}\\%
\pgfutilensurermath {2.62\cdot 10^5}&\pgfutilensurermath {3.81\cdot 10^{-6}}\\%
\pgfutilensurermath {1.05\cdot 10^6}&\pgfutilensurermath {9.54\cdot 10^{-7}}\\%
\end {tabular}%
```

The command `\pgfutilensurermath` checks whether math mode is active and switches to math mode if necessary³.

`/pgfplots/table/include outfiles={boolean}` (initially false)

If enabled, any already existing outfile will be `\input` instead of overwritten.

```
\pgfplotstableset{include outfiles} % for example in the document's preamble
```

This allows to place any corrections manually into generated output files.

³Please note that `\pgfutilensurermath` needs to be replaced by `\ensurermath` if you want to use the output file independent of PGF. That can be done by `\let\pgfutilensurermath=\ensurermath` which enables the L^AT_EX-command `\ensurermath`.

`/pgfplots/table/force remake={\langle boolean \rangle}` (initially false)

If enabled, the effect of `include outfiles` is disabled. As all key settings only last until the next brace (or `\end{\}`), this key can be used to re-generate some output files while others are still included.

`/pgfplots/table/write to macro={\langle macroname \rangle}`

If the value of `write to macro` is not empty, the completely generated (tabular) code will be written into the macro `{\langle macroname \rangle}`.

`/pgfplots/table/skip coltypes=true|false` (initially false)

Allows to skip the `{\langle coltypes \rangle}` in `\begin{tabular}{\langle coltypes \rangle}`. This allows simplifications for other table types which don't have L^AT_EX's table format.

`/pgfplots/table/typeset=true|false` (initially true)

A boolean which disables the final typesetting stage. Use `typeset=false` in conjunction with `write to macro` if only the generated code is of interest and T_EX should not attempt to produce any content in the output pdf.

`/pgfplots/table/debug={\langle boolean \rangle}` (initially false)

If enabled, will write every final tabular code to your log file.

`/pgfplots/table/TeX comment={\langle comment sign \rangle}` (initially %)

The comment sign which is inserted into outfiles to suppress trailing white spaces.

As last example, we use PGFPLOTS_{TABLE} to write an .html (without number formatting, however):

```
<table>
<tr><td>level</td><td>dof</td></tr>
<tr><td>1</td><td>4</td></tr>
<tr><td>2</td><td>16</td></tr>
<tr><td>3</td><td>64</td></tr>
<tr><td>4</td><td>256</td></tr>
<tr><td>5</td><td>1024</td></tr>
<tr><td>6</td><td>4096</td></tr>
<tr><td>7</td><td>16384</td></tr>
<tr><td>8</td><td>65536</td></tr>
<tr><td>9</td><td>262144</td></tr>
<tr><td>10</td><td>1048576</td></tr>
</table>
```

```
\pgfplotstabletypeset[
  begin table={\table}, end table={\table},
  typeset cell/.style={
    /pgfplots/table/@cell content={\td>#1</td>}
  ],
  before row=<tr>,after row=</tr>,
  skip coltypes, typeset=false, string type,
  TeX comment=,
  columns={level,dof},
  outfile=pgfplotstable.example1.out.html,
]{pgfplotstable.example1.dat}
\lstinputlisting
[basicstyle=\ttfamily\footnotesize]
{pgfplotstable.example1.out.html}
```

2.5 Defining Column Types for tabular

Besides input of text files, it is sometimes desirable to define column types for existing `tabular` environments.

`\newcolumntype{\langle letter \rangle}[\langle number of arguments \rangle]>\langle before column \rangle\langle column type \rangle<\langle after column \rangle`

The command `\newcolumntype` is part of the `array` package and it defines a new column type `{\langle letter \rangle}` for use in L^AT_EX tabular environments.

```
\usepackage{array}
```

```
-a+ b \newcolumntype{d}{>{-}c<{+}}
-c+ d \begin{tabular}{dl}
a & b \\
c & d \\
\end{tabular}
```

Now, the environment `pgfplotstablecoltype` can be used in `{\langle before column \rangle}` and `{\langle after column \rangle}` to define numerical columns:

9	2.50 ₋₁	% requires \usepackage{array}
25	6.25 ₋₂	\newcolumnntype{L}[1]
81	1.56 ₋₂	<{\begin{pgfplotstablecoltype}[#1]}r<{\end{pgfplotstablecoltype}}}
289	3.91 ₋₃	\begin{tabular}[L{int detect}]L{sci,sci subscript,sci zerofill}}
1,089	9.77 ₋₄	9 & 2.50000000e-01\\
4,225	2.44 ₋₄	25 & 6.25000000e-02\\
16,641	6.10 ₋₅	81 & 1.56250000e-02\\
66,049	1.53 ₋₅	289 & 3.90625000e-03\\
263,169	3.81 ₋₆	1089 & 9.76562500e-04\\
1,050,625	9.54 ₋₇	4225 & 2.44140625e-04\\
		16641 & 6.10351562e-05\\
		66049 & 1.52587891e-05\\
		263169 & 3.81469727e-06\\
		1050625 & 9.53674316e-07\\
		\end{tabular}

The environment `pgfplotstablecoltype` accepts an optional argument which may contain any number formatting options. It is an error if numerical columns contain non-numerical data, so it may be necessary to use `\multicolumn` for column names.

Dof	Error	% requires \usepackage{array}
9	2.50 ₋₁	\newcolumnntype{L}[1]
25	6.25 ₋₂	<{\begin{pgfplotstablecoltype}[#1]}r<{\end{pgfplotstablecoltype}}}
81	1.56 ₋₂	\begin{tabular}[L{int detect}]L{sci,sci subscript,sci zerofill}}
289	3.91 ₋₃	\multicolumn{1}{r}{Dof} & \multicolumn{1}{r}{Error}\\
1,089	9.77 ₋₄	9 & 2.50000000e-01\\
4,225	2.44 ₋₄	25 & 6.25000000e-02\\
16,641	6.10 ₋₅	81 & 1.56250000e-02\\
66,049	1.53 ₋₅	289 & 3.90625000e-03\\
263,169	3.81 ₋₆	1089 & 9.76562500e-04\\
1,050,625	9.54 ₋₇	4225 & 2.44140625e-04\\
		16641 & 6.10351562e-05\\
		66049 & 1.52587891e-05\\
		263169 & 3.81469727e-06\\
		1050625 & 9.53674316e-07\\
		\end{tabular}

2.6 Number Formatting Options

The following extract of [1] explains how to configure number formats. The common option prefix `/pgf/number format` can be omitted; it will be recognised automatically.

`\pgfmathprintnumber{<x>}`

Generates pretty-printed output for the (real) number `{<x>}`. The input number `{<x>}` is parsed using `\pgfmathfloatparsenumber` which allows arbitrary precision.

Numbers are typeset in math mode using the current set of number printing options, see below. Optional arguments can also be provided using `\pgfmathprintnumber[<options>]{<x>}`.

`\pgfmathprintnumberto{<x>}{\macro}`

Returns the resulting number into `{\macro}` instead of typesetting it directly.

`/pgf/number format/fixed`

(no value)

Configures `\pgfmathprintnumber` to round the number to a fixed number of digits after the period, discarding any trailing zeros.

4.57 0 0.1 24,415.98 123,456.12

```
\pgfkeys{/pgf/number format/.cd, fixed, precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}
```

See section 2.6.1 for how to change the appearance.

`/pgf/number format/fixed zerofill={\langle boolean \rangle}` (default `true`)

Enables or disables zero filling for any number drawn in fixed point format.

4.57 0.00 0.10 24,415.98 123,456.12

```
\pgfkeys{/pgf/number format/.cd,fixed,fixed zerofill,precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}
```

This key affects numbers drawn with `fixed` or `std` styles (the latter only if no scientific format is chosen).

4.57 $5 \cdot 10^{-5}$ 1.00 $1.23 \cdot 10^5$

```
\pgfkeys{/pgf/number format/.cd,std,fixed zerofill,precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-05}\hspace{1em}
\pgfmathprintnumber{1}\hspace{1em}
\pgfmathprintnumber{123456.12345}
```

See section 2.6.1 for how to change the appearance.

`/pgf/number format/sci` (no value)

Configures `\pgfmathprintnumber` to display numbers in scientific format, that means sign, mantisse and exponent (basis 10). The mantisse is rounded to the desired precision.

$4.57 \cdot 10^0$ $5 \cdot 10^{-4}$ $1 \cdot 10^{-1}$ $2.44 \cdot 10^4$ $1.23 \cdot 10^5$

```
\pgfkeys{/pgf/number format/.cd,sci,precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}
```

See section 2.6.1 for how to change the exponential display style.

`/pgf/number format/sci zerofill={\langle boolean \rangle}` (default `true`)

Enables or disables zero filling for any number drawn in scientific format.

$4.57 \cdot 10^0$ $5.00 \cdot 10^{-4}$ $1.00 \cdot 10^{-1}$ $2.44 \cdot 10^4$ $1.23 \cdot 10^5$

```
\pgfkeys{/pgf/number format/.cd,sci,sci zerofill,precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}
```

As with `fixed zerofill`, this option does only affect numbers drawn in `sci` format (or `std` if the scientific format is chosen).

See section 2.6.1 for how to change the exponential display style.

`/pgf/number format/zerofill={\langle boolean \rangle}` (style, default `true`)

Sets both, `fixed zerofill` and `sci zerofill` at once.

`/pgf/number format/std` (no value)

Configures `\pgfmathprintnumber` to a standard algorithm. It chooses either `fixed` or `sci`, depending on the order of magnitude. Let $n = s \cdot m \cdot 10^e$ be the input number and p the current precision. If $-p/2 \leq e \leq 4$, the number is displayed using the fixed format. Otherwise, it is displayed using the scientific format.

4.57 $5 \cdot 10^{-4}$ 0.1 24,415.98 $1.23 \cdot 10^5$

```

\pgfkeys{/pgf/number format/.cd,std,precision=2}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}

```

/pgf/number format/int detect (no value)

Configures `\pgfmathprintnumber` to detect integers automatically. If the input number is an integer, no period is displayed at all. If not, the scientific format is chosen.

```
15 20 2.04 · 101 1 · 10-2 0
```

```

\pgfkeys{/pgf/number format/.cd,int detect,precision=2}
\pgfmathprintnumber{15}\hspace{1em}
\pgfmathprintnumber{20}\hspace{1em}
\pgfmathprintnumber{20.4}\hspace{1em}
\pgfmathprintnumber{0.01}\hspace{1em}
\pgfmathprintnumber{0}

```

/pgf/number format/int trunc (no value)

Truncates every number to integers (discards any digit after the period).

```
4 0 0 24,415 123,456
```

```

\pgfkeys{/pgf/number format/.cd,int trunc}
\pgfmathprintnumber{4.568}\hspace{1em}
\pgfmathprintnumber{5e-04}\hspace{1em}
\pgfmathprintnumber{0.1}\hspace{1em}
\pgfmathprintnumber{24415.98123}\hspace{1em}
\pgfmathprintnumber{123456.12345}

```

/pgf/number format/precision={*number*}

Sets the desired rounding precision for any display operation. For scientific format, this affects the mantisse.

2.6.1 Changing Number Format Display Styles

You can change the way how numbers are displayed. For example, if you use the ‘fixed’ style, the input number is rounded to the desired precision and the current fixed point display style is used to typeset the number. The same is applied to any other format: first, rounding routines are used to get the correct digits, afterwards a display style generates proper \TeX -code.

/pgf/number format/set decimal separator={*text*}

Assigns `{text}` as decimal separator for any fixed point numbers (including the mantisse in sci format).

/pgf/number format/dec sep={*text*}

Just another name for `set decimal separator`.

/pgf/number format/set thousands separator={*text*}

Assigns `{text}` as thousands separator for any fixed point numbers (including the mantisse in sci format).

```

1234.56 \pgfkeys{/pgf/number format/.cd,
fixed,
fixed zerofill,
precision=2,
set thousands separator={}}
\pgfmathprintnumber{1234.56}

```

```

1234567890.00 \pgfkeys{/pgf/number format/.cd,
fixed,
fixed zerofill,
precision=2,
set thousands separator={}}
\pgfmathprintnumber{1234567890}

```

1.234.567.890.00	\pgfkeys{/pgf/number format/.cd, fixed, fixed zerofill, precision=2, set thousands separator={.}} \pgfmathprintnumber{1234567890}
------------------	--

1,234,567,890.00	\pgfkeys{/pgf/number format/.cd, fixed, fixed zerofill, precision=2, set thousands separator={,}} \pgfmathprintnumber{1234567890}
------------------	--

1,234,567,890.00	\pgfkeys{/pgf/number format/.cd, fixed, fixed zerofill, precision=2, set thousands separator={{{,}}}} \pgfmathprintnumber{1234567890}
------------------	--

The last example employs commas and disables the default comma-spacing.

`/pgf/number format/1000 sep={text}`

Just another name for `set thousands separator`.

`/pgf/number format/min exponent for 1000 sep={number}` (initially 0)

Defines the smallest exponent in scientific notation which is required to draw thousand separators. The exponent is the number of digits minus one, so $\langle number \rangle = 4$ will use thousand separators starting with $1e4 = 10000$.

5 000; 1 000 000	\pgfkeys{/pgf/number format/.cd, int detect, 1000 sep={\,}, min exponent for 1000 sep=0} \pgfmathprintnumber{5000}; \pgfmathprintnumber{1000000}
------------------	--

1000; 5000	\pgfkeys{/pgf/number format/.cd, int detect, 1000 sep={\,}, min exponent for 1000 sep=4} \pgfmathprintnumber{1000}; \pgfmathprintnumber{5000}
------------	---

10 000; 1 000 000	\pgfkeys{/pgf/number format/.cd, int detect, 1000 sep={\,}, min exponent for 1000 sep=4} \pgfmathprintnumber{10000}; \pgfmathprintnumber{1000000}
-------------------	---

A value of 0 disables this feature (negative values are ignored).

`/pgf/number format/use period` (no value)

A predefined style which installs periods ‘.’ as decimal separators and commas ‘,’ as thousands separators. This style is the default.

12.35	\pgfkeys{/pgf/number format/.cd,fixed,precision=2,use period} \pgfmathprintnumber{12.3456}
-------	---

1,234.56	\pgfkeys{/pgf/number format/.cd,fixed,precision=2,use period} \pgfmathprintnumber{1234.56}
----------	---

`/pgf/number format/use comma` (no value)

A predefined style which installs commas ‘,’ as decimal separators and periods ‘.’ as thousands separators.

```
12,35 \pgfkeys{/pgf/number format/.cd,fixed,precision=2,use comma}
\pgfmathprintnumber{12.3456}
```

```
1.234,56 \pgfkeys{/pgf/number format/.cd,fixed,precision=2,use comma}
\pgfmathprintnumber{1234.56}
```

`/pgf/number format/skip 0.=`{*boolean*} (initially false)

Configures whether numbers like 0.1 shall be typeset as .1 or not.

```
.56 \pgfkeys{/pgf/number format/.cd,
fixed,
fixed zerofill,precision=2,
skip 0.}
\pgfmathprintnumber{0.56}
```

```
0.56 \pgfkeys{/pgf/number format/.cd,
fixed,
fixed zerofill,precision=2,
skip 0.=false}
\pgfmathprintnumber{0.56}
```

`/pgf/number format/showpos=`{*boolean*} (initially false)

Enables or disables display of plus signs for non-negative numbers.

```
+12.35 \pgfkeys{/pgf/number format/showpos}
\pgfmathprintnumber{12.345}
```

```
12.35 \pgfkeys{/pgf/number format/showpos=false}
\pgfmathprintnumber{12.345}
```

```
+1.23 · 101 \pgfkeys{/pgf/number format/.cd,showpos,sci}
\pgfmathprintnumber{12.345}
```

`/pgf/number format/print sign=`{*boolean*}

A style which is simply an alias for `showpos={boolean}`.

`/pgf/number format/sci 10e` (no value)

Uses $m \cdot 10^e$ for any number displayed in scientific format.

```
1.23 · 101 \pgfkeys{/pgf/number format/.cd,sci,sci 10e}
\pgfmathprintnumber{12.345}
```

`/pgf/number format/sci 10e` (no value)

The same as ‘`sci 10e`’.

`/pgf/number format/sci e` (no value)

Uses the ‘`1e+0`’ format which is generated by common scientific tools for any number displayed in scientific format.

```
1.23e+1 \pgfkeys{/pgf/number format/.cd,sci,sci e}
\pgfmathprintnumber{12.345}
```

`/pgf/number format/sci E` (no value)
The same with an uppercase ‘E’.

```
1.23E+1 \pgfkeys{/pgf/number format/.cd,sci,sci E}  
\pgfmathprintnumber{12.345}
```

`/pgf/number format/sci subscript` (no value)
Typesets the exponent as subscript for any number displayed in scientific format. This style requires very few space.

```
1.231 \pgfkeys{/pgf/number format/.cd,sci,sci subscript}  
\pgfmathprintnumber{12.345}
```

`/pgf/number format/sci superscript` (no value)
Typesets the exponent as superscript for any number displayed in scientific format. This style requires very few space.

```
1.231 \pgfkeys{/pgf/number format/.cd,sci,sci superscript}  
\pgfmathprintnumber{12.345}
```

`/pgf/number format/@dec sep mark={\langle text \rangle}`
Will be placed right before the place where a decimal separator belongs to. However, `{\langle text \rangle}` will be inserted even if there is no decimal separator. It is intended as place-holder for auxiliary routines to find alignment positions.
This key should never be used to change the decimal separator! Use `dec sep` instead.

`/pgf/number format/@sci exponent mark={\langle text \rangle}`
Will be placed right before exponents in scientific notation. It is intended as place-holder for auxiliary routines to find alignment positions.
This key should never be used to change the exponent!

`/pgf/number format/assume math mode={\langle boolean \rangle}` (default `true`)
Set this to `true` if you don’t want any checks for math mode.
The initial setting installs a `\pgfutilensuremath` around each final number to change to math mode if necessary. Use `assume math mode=true` if you know that math mode is active and you don’t want `\pgfutilensuremath`.

3 Fine Tuning of Loaded Data

The conversion from an unprocessed input table to a final typesetted `tabular` code uses four stages for every cell,

1. Loading the table,
2. Preprocessing,
3. Typesetting,
4. Postprocessing.

The main idea is to select one typesetting algorithm (for example “format my numbers with the configured number style”). This algorithm usually doesn’t need to be changed. Fine tuning can then be done using zero, one or more preprocessors and postprocessors. Preprocessing can mean to select only particular rows or to apply some sort of operation before the typesetting algorithm sees the content. Postprocessing means to apply fine-tuning to the resulting `TeX` output – for example to deal with empty cells or to insert unit suffixes or modify fonts for single cells.

3.1 Loading the table

This first step to typeset a table involves the obvious input operations. Furthermore, the “new column creation” operations explained in section 4 are processed at this time. The table data is read (or acquired) as already explained earlier in this manual. Then, if columns are missing, column alias and `create on use` specifications will be processed as part of the loading procedure. See section 4 for details about column creation.

3.2 Typesetting Cell Content

Typesetting cells means to take their value and “do something”. In many cases, this involves number formatting routines. For example, the “raw” input data 12.56 might become $1.235 \cdot 10^1$. The result of this stage is no longer useful for content-based computations. The typesetting step follows the preprocessing step.

`/pgfplots/table/assign cell content/.code={\dots}`

Allows to redefine the algorithm which assigns cell contents. The argument `#1` is the (unformatted) contents of the input table.

The resulting output needs to be written to `/pgfplots/table/@cell content`.

Please note that you may need special attention for `#1={}`, i.e. the empty string. This may happen if a column has less rows than the first column. PGFPLOTS/TABLE will balance columns automatically in this case, inserting enough empty cells to match the number of rows of the first column.

Please note further that if any column has more entries than the first column, these entries will be skipped and a warning message will be issued into the log file.

This key is evaluated inside of a local \TeX group, so any local macro assignments will be cleared afterwards.

`/pgfplots/table/assign cell content as number` (no value)

This here is the default implementation of `assign cell contents`.

It invokes `\pgfmathprintnumber` to and writes the result into `@cell content`.

`/pgfplots/table/string type` (style, no value)

A style which redefines `assign cell contents` to simply return the “raw” input data, that means as text column. This assumes input tables with valid \LaTeX content (verbatim printing is not supported).

`/pgfplots/table/date type={\langle date format \rangle}`

A style which expects ISO dates of the form YYYY-MM-DD in each cell and produces pretty-printed strings on output. The output format is given as `{\langle date format \rangle}`. Inside of `{\langle date format \rangle}`, several macros which are explained below can be used.

date	account1	date	account1
2008-01-03	60	January 2008	60
2008-02-06	120	February 2008	120
2008-03-15	-10	March 2008	-10
2008-04-01	1,800	April 2008	1,800
2008-05-20	2,300	May 2008	2,300
2008-06-15	800	June 2008	800

```
% Requires
% \usepackage{pgfcalendar}
\pgfplotstableset{columns={date,account1}}

\pgfplotstabletypeset[
  columns/date/.style={string type}
]{plotdata/accounts.dat}
\hspace{1cm}
\pgfplotstabletypeset[
  columns/date/.style={date type={\monthname\ \year}}
]{plotdata/accounts.dat}
```

This style **requires** to load the PGF **calendar package**:

```
\usepackage{pgfcalendar}
```

`\year`

Inside of $\{\langle date format \rangle\}$, this macro expands to the year as number (like 2008).

`\month`

Inside of $\{\langle date format \rangle\}$, this macro expands to the month as number, starting with 1 (like 1).

`\monthname`

Inside of $\{\langle date format \rangle\}$, this macro expands to the month's name as set in the current language (like January). See below for how to change the language.

`\monthshortname`

Inside of $\{\langle date format \rangle\}$, this macro expands to the month's short name as set in the current language (like Jan). See below for how to change the language.

`\day`

Inside of $\{\langle date format \rangle\}$, this macro expands to the day as number (like 31).

`\weekday`

Inside of $\{\langle date format \rangle\}$, this macro expands to the weekday number (0 for Monday, 1 for Tuesday etc.).

`\weekdayname`

Inside of $\{\langle date format \rangle\}$, this macro expands to the weekday's name in the current language (like Wednesday). See below for how to change the language.

`\weekdayshortname`

Inside of $\{\langle date format \rangle\}$, this macro expands to the weekday's short name in the current language (like Wed). See below for how to change the language.

Changing the language for dates

The date feature is implemented using the PGF calendar module. This module employs the package `translator` (if it is loaded). I don't have more detail yet, sorry. Please refer to [1] for more details.

3.3 Preprocessing Cell Content

The preprocessing step allows to change cell contents *before* any typesetting routine (like number formatting) has been applied. The data is available in numerical format and math operations can be applied. Furthermore, cells can be erased depending on their numerical value. The preprocess step follows the data acquisition step ("loading step"). This means in particular that you can create (or copy) columns and apply operations on them.

```
/pgfplots/table/preproc cell content/.code={\dots}
```

Allows to *modify* the contents of cells *before* `assign cell contents` is called.

The semantics is as follows: before the preprocessor, `@cell content` contains the raw input data (or, maybe, the result of another preprocessor call). After the preprocessor, `@cell content` is filled with a – possibly modified – value. The resulting value is then used as input to `assign cell contents`.

In the default settings, `assign cell contents` expects numerical input. So, the preprocessor is expected to produce numerical output.

It is possible to provide multiple preprocessor directives using `.append code` or `.append style` key handlers.

In case you don't want (or need) stackable preprocessors, you can also use `'#1'` to get the raw input datum as it is found in the file.

`/pgfplots/table/string replace={⟨pattern⟩}{⟨replacement⟩}`

Appends code to the current `preproc cell content` value which replace every occurrence of `{⟨pattern⟩}` with `{⟨replacement⟩}`. No expansion is performed during this step; `{⟨pattern⟩}` must match literally.

level	dof	level	dof
1	4	1	4
2	16	2	16
3	64	3	64
4	256	4	-42
5	1,024	5	1,024
6	4,096	6	4,096
7	16,384	7	16,384
8	65,536	8	65,536
9	$2.62 \cdot 10^5$	9	$2.62 \cdot 10^5$
10	$1.05 \cdot 10^6$	10	$1.05 \cdot 10^6$

```
\pgfplotstabletypeset[columns={level,dof}]
{pgfplotstable.example1.dat}
```

```
\pgfplotstabletypeset[
columns={level,dof},
columns/level/.style={string replace={A}{B}}, % does nothing because there is no 'A'
columns/dof/.style={string replace={256}{-42}}] % replace '256' with '-42'
{pgfplotstable.example1.dat}
```

`/pgfplots/table/clear infinite` (style, no value)

Appends code to the current `preproc cell content` value which replaces every infinite number with the empty string. This clears any cells with $\pm\infty$ and NaN.

`/pgfplots/table/multiply with={⟨real number⟩}`

Appends code to the current `preproc cell content` value which multiplies every cell with `{⟨real number⟩}`. Arithmetics are carried out in floating point.

`/pgfplots/table/divide by={⟨real number⟩}`

Appends code to the current `preproc cell content` value which divides every cell by `{⟨real number⟩}`. Arithmetics are carried out in floating point.

`/pgfplots/table/sqrt` (style, no value)

Appends code to the current `preproc cell content` value which applies \sqrt{x} to every non-empty cell. Arithmetics are carried out in floating point.

The following example copies the column `error1` and applies `sqrt` to the copy.

ϵ	$\sqrt{\epsilon}$
$2.500 \cdot 10^{-1}$	$5.000 \cdot 10^{-1}$
$6.250 \cdot 10^{-2}$	$2.500 \cdot 10^{-1}$
$1.563 \cdot 10^{-2}$	$1.250 \cdot 10^{-1}$
$3.906 \cdot 10^{-3}$	$6.250 \cdot 10^{-2}$
$9.766 \cdot 10^{-4}$	$3.125 \cdot 10^{-2}$
$2.441 \cdot 10^{-4}$	$1.562 \cdot 10^{-2}$
$6.104 \cdot 10^{-5}$	$7.813 \cdot 10^{-3}$
$1.526 \cdot 10^{-5}$	$3.906 \cdot 10^{-3}$
$3.815 \cdot 10^{-6}$	$1.953 \cdot 10^{-3}$
$9.537 \cdot 10^{-7}$	$9.766 \cdot 10^{-4}$

```
\pgfplotstableset{
columns={error1,sqrterror1},
create on use/sqrterror1/.style={create col/copy=error1},
columns/error1/.style={column name=$\epsilon$},
columns/sqrterror1/.style={sqrt,column name=$\sqrt{\epsilon}$},
sci,sci 10e,precision=3,sci zerofill
}
\pgfplotstabletypeset{pgfplotstable.example1.dat}
```

Please take a look at section 4 for details about `create on use`.

`/pgfplots/table/multiply -1`

(style, no value)

Appends code to current `preproc cell` content value which multiplies every cell with -1 . This style does the same job as `multiply with=-1`, it is just faster because only the sign changes.

dof	error2	slopes2	dof	error2	slopes2
4	$7.58 \cdot 10^{-1}$	–	4	$7.58 \cdot 10^{-1}$	–
16	$5.00 \cdot 10^{-1}$	–0.3	16	$5.00 \cdot 10^{-1}$	0.3
64	$2.87 \cdot 10^{-1}$	–0.4	64	$2.87 \cdot 10^{-1}$	0.4
256	$1.44 \cdot 10^{-1}$	–0.5	256	$1.44 \cdot 10^{-1}$	0.5
1,024	$4.42 \cdot 10^{-2}$	–0.85	1,024	$4.42 \cdot 10^{-2}$	0.85
4,096	$1.70 \cdot 10^{-2}$	–0.69	4,096	$1.70 \cdot 10^{-2}$	0.69
16,384	$8.20 \cdot 10^{-3}$	–0.52	16,384	$8.20 \cdot 10^{-3}$	0.52
65,536	$3.91 \cdot 10^{-3}$	–0.54	65,536	$3.91 \cdot 10^{-3}$	0.54
$2.62 \cdot 10^5$	$1.95 \cdot 10^{-3}$	–0.5	$2.62 \cdot 10^5$	$1.95 \cdot 10^{-3}$	0.5
$1.05 \cdot 10^6$	$9.77 \cdot 10^{-4}$	–0.5	$1.05 \cdot 10^6$	$9.77 \cdot 10^{-4}$	0.5

```
\pgfplotstableset{
  columns={dof,error2,slopes2},
  columns/error2/.style={sci,sci zerofill},
  columns/slopes2/.style={dec sep align,empty cells with={\ensuremath{-}}},
  create on use/slopes2/.style=
    {create col/gradient loglog={dof}{error2}}
}

\pgfplotstabletypeset{pgfplotstable.example1.dat}

\pgfplotstabletypeset[columns/slopes2/.append style={multiply -1}]
{pgfplotstable.example1.dat}
```

`/pgfplots/table/row predicate/.code={\langle... \rangle}`

A boolean predicate which allows to select particular rows of the input table. The argument `#1` contains the current row's index (starting with 0, not counting comment lines or column names).

The return value is assigned to the \TeX -if `\ifpgfplotstableuserow`. If the boolean is not changed, the return value is true.

level	dof	error1	error2	info	grad(log(dof),log(error2))	quot(error1)
1	4	0.25	0.76	48	0	0
2	16	$6.25 \cdot 10^{-2}$	0.5	25	–0.3	4
3	64	$1.56 \cdot 10^{-2}$	0.29	41	–0.4	4
4	256	$3.91 \cdot 10^{-3}$	0.14	8	–0.5	4
5	1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	22	–0.85	4
9	$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	33	–0.5	4
10	$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	–0.5	4

```
% requires \usepackage{booktabs}
\pgfplotstabletypeset[
  every head row/.style={
    before row=\toprule,after row=\midrule},
  every last row/.style={
    after row=\bottomrule},
  row predicate/.code={%
    \ifnum#1>4\relax
      \ifnum#1<8\relax
        \pgfplotstableuserowfalse
      \fi
    \fi}
]
{pgfplotstable.example1.dat}
```

Please note that `row predicate` is applied *before* any other option which affects row appearance. It is evaluated before `assign cell contents`. For example, the even/odd row styles refer to those rows for which the predicate returns true. In fact, you can use `row predicate` to truncate the complete table before it as actually processed.

During row predicate, the macro `\pgfplotstablerows` contains the total number of *input* rows.

Furthermore, `row predicate` applies only to the typeset routines, not the read methods. If you want to plot only selected table entries with `\addplot table`, use the PGFPLOTS coordinate filter options.

`/pgfplots/table/skip rows between index= $\langle begin \rangle$ $\langle end \rangle$`

A style which appends an `row predicate` which discards selected rows. The selection is done by index where indexing starts with 0. Every row with index $\langle begin \rangle \leq i < \langle end \rangle$ will be skipped.

level	dof	error1	error2	info	grad(log(dof),log(error2))	quot(error1)
1	4	0.25	0.76	48	0	0
2	16	$6.25 \cdot 10^{-2}$	0.5	25	-0.3	4
5	1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	22	-0.85	4
6	4,096	$2.44 \cdot 10^{-4}$	$1.7 \cdot 10^{-2}$	46	-0.69	4
7	16,384	$6.1 \cdot 10^{-5}$	$8.2 \cdot 10^{-3}$	40	-0.52	4
10	$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	-0.5	4

```
% requires \usepackage{booktabs}
\pgfplotstableread[
  every head row/.style={
    before row=\toprule,after row=\midrule},
  every last row/.style={
    after row=\bottomrule},
  skip rows between index={2}{4},
  skip rows between index={7}{9}
]
{pgfplotstable.example1.dat}
```

`/pgfplots/table/select equal part entry of= $\langle part no \rangle$ $\langle part count \rangle$`

A style which overwrites `row predicate` with a subset selection predicate. The idea is to split the current column into $\langle part count \rangle$ equally sized parts and select only $\langle part no \rangle$.

This can be used to simulate multicolumn tables.

A	B				
A1	B1				
A2	B2				
A3	B3				
A4	B4				
A5	B5	A	B	A	B
A6	B6	A1	B1	A12	B12
A7	B7	A2	B2	A13	B13
A8	B8	A3	B3	A14	B14
A9	B9	A4	B4	A15	B15
A10	B10	A5	B5	A16	B16
A11	B11	A6	B6	A17	B17
A12	B12	A7	B7	A18	B18
A13	B13	A8	B8	A19	B19
A14	B14	A9	B9	A20	B20
A15	B15	A10	B10	A21	B21
A16	B16	A11	B11		
A17	B17				
A18	B18				
A19	B19				
A20	B20				
A21	B21				

```

% requires \usepackage{booktabs}
\pgfplotstableset{
  every head row/.style={before row=\toprule,after row=\midrule},
  every last row/.style={after row=\bottomrule}}

\pgfplotstabletypeset[string type]{pgfplotstable.example2.dat}

\pgfplotstabletypeset[
  display columns/0/.style={select equal part entry of={0}{2},string type},
  display columns/1/.style={select equal part entry of={0}{2},string type},
  display columns/2/.style={select equal part entry of={1}{2},string type},
  display columns/3/.style={select equal part entry of={1}{2},string type},
  columns={A,B,A,B}
]
{pgfplotstable.example2.dat}

```

The example above shows the original file as-is on the left side. The right side shows columns A,B,A,B – but only half of the elements are shown, selected by indices #0 or #1 of #2. The parts are equally large, up to a remainder.

If the available number of rows is not dividable by $\langle part\ count \rangle$, the remaining entries are distributed equally among the first parts.

3.4 Postprocessing Cell Content

The postprocessing step is applied after the typesetting stage, that means it can't access the original input data. However, it can apply final formatting instructions which are not content based.

`/pgfplots/table/postproc cell content/.code={\langle... \rangle}`

Allows to *modify* assigned cell content *after* it has been assigned, possibly content-dependent. Ideas could be to draw negative numbers in red, typeset single entries in bold face or insert replacement text.

This key is evaluated *after assign cell content*. Its semantics is to modify an existing `@cell content` value.

There may be more than one `postproc cell content` command, if you use `.append code` or `.append style` to define them:

<pre> dof info 4 48€ 16 25€ 64 41€ 256 8€ 1,024 22€ 4,096 46€ 16,384 40€ 65,536 48€ 2.62 · 10⁵ 33€ 1.05 · 10⁶ 2€ </pre>	<pre> % requires \usepackage{eurosym} \pgfplotstabletypeset[column type=r, columns={dof,info}, columns/info/.style={ postproc cell content/.append style={ /pgfplots/table/@cell content/.add={\bf}{\\$}}, postproc cell content/.append style={ /pgfplots/table/@cell content/.add={}\{EUR{}}}}] {pgfplotstable.example1.dat} </pre>
--	---

The code above modifies `@cell content` successively. First, “`\bf ... $`” is inserted, then “`... \EUR`”. It should be noted that `pgfkeys` handles `.style` and `.code` in (quasi) the same way – both are simple code keys and can be used as such. You can combine both with `.append style` and `.append code`. Please refer to [1, section about `pgfkeys`] for details.

As in `assign cell contents`, the code can evaluate helper macros like `\pgfplotstablerow` to change only particular entries. Furthermore, the argument “#1” expands to the *unformatted* input argument which was found in the input table. This allows complete context based formatting options. Please remember that empty strings may appear due to column balancing – introduce special treatment if necessary.

There is one special case which occurs if `@cell content` itself contains the cell separation character ‘&’. In this case, `postproc cell contents` is invoked *separately* for each part before and after the ampersand and the ampersand is inserted afterwards. This allows compatibility with special styles which create artificial columns in the output (which is allowed, see `dec sep align`). To allow separate treatment of each part, you can use the macro `\pgfplotstablepartno`. It is defined only during the

evaluation of `postproc cell content` and it evaluates to the current part index (starting with 0). If there is no ampersand in your text, the value will always be 0.

This key is evaluated inside of a local \TeX group, so any local macro assignments will be cleared afterwards.

The following example can be used to insert a dash, $-$, in a slope column:

dof	error1	slopes1
4	$2.50 \cdot 10^{-1}$	$-$
16	$6.25 \cdot 10^{-2}$	-1
64	$1.56 \cdot 10^{-2}$	-1
256	$3.91 \cdot 10^{-3}$	-1
1,024	$9.77 \cdot 10^{-4}$	-1
4,096	$2.44 \cdot 10^{-4}$	-1
16,384	$6.10 \cdot 10^{-5}$	-1
65,536	$1.53 \cdot 10^{-5}$	-1
$2.62 \cdot 10^5$	$3.81 \cdot 10^{-6}$	-1
$1.05 \cdot 10^6$	$9.54 \cdot 10^{-7}$	-1

```

\pgfplotstableset{
  create on use/slopes1/.style=
    {create col/gradient loglog={dof}{error1}}
}

\pgfplotstabletypeset[
  columns={dof,error1,slopes1},
  columns/error1/.style={sci,sci zerofill},
  columns/slopes1/.style={
    postproc cell content/.append code={%
      \ifnum\pgfplotstablerow=0
        \pgfkeyssetvalue{/pgfplots/table/@cell content}{\ensuremath{-}}%
      \fi
    }%
  }
]{pgfplotstable.example1.dat}

```

Since this may be useful in a more general context, it is available as `empty cells with style`.

`/pgfplots/table/empty cells with={\replacement}`

Appends code to `postproc cell content` which replaces any empty cell with `{\replacement}`.

If `dec sep align` is active, the replacement will be inserted only for the part before the decimal separator.

`/pgfplots/table/set content={\content}`

A style which redefines `postproc cell contents` to always return the value `{\content}`.

4 Generating Data in New Tables or Columns

It is possible to create new tables from scratch or to change tables after they have been loaded from disk.

4.1 Creating New Tables From Scratch

`\pgfplotstablenew[options]{\row count}{\table}`

Creates a new table from scratch.

The new table will contain all columns listed in the `columns` key which needs to be provided in `[options]`⁴.

Furthermore, there must be `create on use` statements (see the next subsection) for every column which shall be generated. Columns are generated independently, in the order of appearance in `columns`.

The table will contain exactly `{\row count}` rows. If `{\row count}` is an `\pgfplotstablegetrows of` statement, that statement will be executed and the resulting number of rows be used. Otherwise, `{\row count}` will be evaluated as number.

⁴Currently, you need to provide at least one column here: the implementation gets confused for completely empty tables. If you do not provide any column name, a dummy column will be created.

new
4
5
6
7
8
9
10
—
—
—
—

```

% this key setting could be provided in the document's preamble:
\pgfplotstableset{
  % define how the 'new' column shall be filled:
  create on use/new/.style={create col/set list={4,5,6,7,...,10}}
}
% create a new table with 11 rows and column 'new':
\pgfplotstablenew[columns={new}]{11}\table
% show it:
\pgfplotstabletypeset[empty cells with={--}]\table

```

new
$1.31 \cdot 10^{12}$
$2.09 \cdot 10^{13}$
$3.56 \cdot 10^{14}$
$6.4 \cdot 10^{15}$
$1.22 \cdot 10^{17}$
$2.43 \cdot 10^{18}$
$5.11 \cdot 10^{19}$
$1.12 \cdot 10^{21}$
$2.59 \cdot 10^{22}$
$6.2 \cdot 10^{23}$
$1.55 \cdot 10^{25}$

```

% create a new table with 11 rows and column 'new':
\pgfplotstablenew[
  % define how the 'new' column shall be filled:
  create on use/new/.style={create col/expr={factorial(15+\pgfplotstablerow)}},
  columns={new}
]{11}
\table
% show it:
\pgfplotstabletypeset\table

```

`\pgfplotstablevertcat`{ $\langle table1 \rangle$ }{ $\langle table2 \text{ or filename} \rangle$ }

Appends the contents of $\langle table2 \rangle$ to $\langle table1 \rangle$ (“vertical cat”). To be more precise, only columns which exist already in $\langle table1 \rangle$ will be appended and every column which exists in $\langle table1 \rangle$ must exist in $\langle table2 \rangle$ (or there must be `alias` or `create on use` specifications to generate them).

If the second argument is a file name, that file will be loaded from disk.

If $\langle table1 \rangle$ does not exist, $\langle table2 \rangle$ will be copied to $\langle table1 \rangle$.

```

\pgfplotstablevertcat{\output}{datafile1} % loads 'datafile1' -> '\output'
\pgfplotstablevertcat{\output}{datafile2} % appends rows of datafile2
\pgfplotstablevertcat{\output}{datafile3} % appends rows of datafile3

```

4.2 Creating New Columns From Existing Ones

`\pgfplotstablecreatecol`[$\langle options \rangle$]{ $\langle new \text{ col name} \rangle$ }{ $\langle table \rangle$ }

Creates a new column named $\langle new \text{ col name} \rangle$ and appends it to an already existing table $\langle table \rangle$.

End users probably don’t need to use `\pgfplotstablecreatecol` directly at all – there is the high-level framework `create on use` which invokes it internally and can be used with simple key–value assignments (see below). However, this documentation explains how to use values of existing columns to fill new cells.

This command offers a flexible framework to generate new columns. It has been designed to create new columns using the already existing values – for example using logical or numerical methods to combine existing values. It provides fast access to a row’s value, the previous row’s value and the next row’s value.

The following documentation is for all who want to *write* specialised columns. It is not particularly difficult; it is just technical and it requires some knowledge of `pgfkeys`. If you don’t like it, you can resort to predefined column generation styles - and enable those styles in $\langle options \rangle$.

The column entries will be created using the command key `create col/assign`. It will be invoked for every row of the table. It is supposed to assign contents to `create col/next content`. During the evaluation, the macro `\thisrow{ $\langle col \text{ name} \rangle$ }` expands to the current row’s value of the column

identified by $\langle col\ name\rangle$. Furthermore, $\backslash nextrow\langle col\ name\rangle$ expands to the *next* row's value of the designated column and $\backslash prevrow\langle col\ name\rangle$ expands to the value of the *previous* row.

So, the idea is to simply redefine the command key `create col/assign` in such a way that it fills new cells as desired.

Two special `assign` routines are available for the first and last row: The contents for the *last* row is computed with `create col/assign last`. Its semantics is the same. The contents for the *first* row is computed with `create col/assign first` to simplify special cases here. These first and last commands are optional, their default is to invoke the normal `assign` routine.

The evaluation of the `assign` keys is done in local T_EX groups (i.e. any local definitions will be cleared afterwards).

The following macros are useful during cell assignments:

1. $\backslash prevrow\langle col\ name\rangle$ / $\backslash getprevrow\langle col\ name\rangle\langle\backslash macro\rangle$
 These two routines return the value stored in the *previous* row of the designated column $\langle col\ name\rangle$. The `get` routine stores it into $\langle\backslash macro\rangle$.
2. $\backslash thisrow\langle col\ name\rangle$ / $\backslash getthisrow\langle col\ name\rangle\langle\backslash macro\rangle$
 These two routines return the *current* row's value stored in the designated column. The `get` routine stores it into $\langle\backslash macro\rangle$.
3. $\backslash nextrow\langle col\ name\rangle$ / $\backslash getnextrow\langle col\ name\rangle\langle\backslash macro\rangle$
 These two routines return the *next* row's value.
4. `\pgfplotstablerow` and `\pgfplotstablerows` which contain the current row's index and the total number of rows, respectively. See page 10 for details.
5. `\pgfmathaccuma` and `\pgfmathaccumb` can be used to transport intermediate results. Both maintain their value from one column assignment to the next. All other local variables will be deleted after leaving the assignment routines. The initial value is the empty string for both of them unless they are already initialised by column creation styles.
6. commands which are valid throughout every part of this package, for example `\pgfplotstablerow` to get the current row index or `\pgfplotstablerows` to get the total number of rows.

The $\langle col\ name\rangle$ is expected to be a *physical* column name, no alias or column index is allowed (unless column indices and column names are the same).

The following example takes our well-known input table and creates a copy of the `level` column. Furthermore, it produces a lot of output to show the available macros. Finally, it uses `\pgfkeyslet` to assign the contents of the resulting `\entry to next content`.

level	new
1	thisrow=1; nextrow=2. (#0/10)
2	thisrow=2; nextrow=3. (#1/10)
3	thisrow=3; nextrow=4. (#2/10)
4	thisrow=4; nextrow=5. (#3/10)
5	thisrow=5; nextrow=6. (#4/10)
6	thisrow=6; nextrow=7. (#5/10)
7	thisrow=7; nextrow=8. (#6/10)
8	thisrow=8; nextrow=9. (#7/10)
9	thisrow=9; nextrow=10. (#8/10)
10	thisrow=10; nextrow=. (#9/10)

```

\pgfplotstableread{pgfplotstable.example1.dat}\table
\pgfplotstablecreatecol[
  create col/assign/.code={%
    \getthisrow{level}\entry
    \getnextrow{level}\nextentry
    \edef\entry{thisrow=\entry; nextrow=\nextentry.
      (\#\pgfplotstablerow/\pgfplotstablerows)}%
    \pgfkeyslet{/pgfplots/table/create col/next content}\entry
  }]
{new}\table

\pgfplotstabletypeset[
  column type=1,
  columns={level,new},
  columns/new/.style={string type}
]\table

```

There is one more speciality: you can use `columns={column list}` to reduce the runtime complexity of this command. This works only if the `columns` key is provided directly into `{options}`. In this case `\thisrow` and its variants are only defined for those columns listed in the `columns` value.

Limitations. Currently, you can only access three values of one column at a time: the current row, the previous row and the next row. Access to arbitrary indices is not (yet) supported. Furthermore, this command has been designed to modify an existing table. You can't create a table from scratch with this command.

The default implementation of `assign` is to produce empty strings. The default implementation of `assign last` is to invoke `assign`, so in case you never really use the next row's value, you won't need to touch `assign last`. The same holds for `assign first`.

`/pgfplots/table/create on use/<col name>/.style={create options}`

Allows “lazy creation” of the column `<col name>`. Whenever the column `<col name>` is queried by name, for example in an `\pgfplotstabletypeset` command, and such a column does not exist already, it is created on-the-fly.

<pre> error1 quot1 2.50 · 10⁻¹ 6.25 · 10⁻² 4 1.56 · 10⁻² 4 3.91 · 10⁻³ 4 9.77 · 10⁻⁴ 4 2.44 · 10⁻⁴ 4 6.10 · 10⁻⁵ 4 1.53 · 10⁻⁵ 4 3.81 · 10⁻⁶ 4 9.54 · 10⁻⁷ 4 </pre>	<pre> % requires \usepackage{array} \pgfplotstableset{% could be used in preamble create on use/quot1/.style= {create col/quotient={error1}}} \pgfplotstabletypeset[columns={error1,quot1}, columns/error1/.style={sci,sci zerofill}, columns/quot1/.style={dec sep align}] {pgfplotstable.example1.dat} </pre>
---	--

The example above queries `quot1` which does not yet exist in the input file. Therefore, it is checked whether a `create on use` style for `quot1` exists. This is the case, so it is used to create the missing column. The `create col/quotient` key is discussed below; it computes quotients of successive rows in column `error1`.

A `create on use` specification is translated into

```
\pgfplotstablecreatecol[create options]{col name}{the table},
```

or, equivalently, into

```
\pgfplotstablecreatecol[create on use/<col name>]{col name}{the table}.
```

This feature allows some laziness, because you can omit the lengthy table modifications. However, laziness may cost something: in the example above, the generated column will be *lost* after returning from `\pgfplotstabletypeset`.

The `create on use` has higher priority than `alias`.

In case `<col name>` contains characters which are required for key settings, you need to use braces around it: “`create on use/{name=with,special}/.style={...}`”.

More examples for `create on use` are shown below while discussing the available column creation styles.

4.3 Predefined Column Generation Methods

The following keys can be used in both `\pgfplotstablecreatecol` and the easier `create on use` frameworks.

4.3.1 Acquiring Data Somewhere

`/pgfplots/table/create col/set= $\langle value \rangle$`

A style for use in column creation context which creates a new column and writes $\langle value \rangle$ into each new cell. The value is written as string (verbatim).

level	my new col	
1	-empty-	<pre>\pgfplotstableset{ create on use/my new col/.style={create col/set={--empty--}}, columns/my new col/.style={string type} } \pgfplotstabletypeset[columns={level,my new col},]{pgfplotstable.example1.dat}</pre>
2	-empty-	
3	-empty-	
4	-empty-	
5	-empty-	
6	-empty-	
7	-empty-	
8	-empty-	
9	-empty-	
10	-empty-	

`/pgfplots/table/create col/set list= $\langle comma-separated-list \rangle$`

A style for use in column creation context which creates a new column consisting of the entries in $\langle comma-separated-list \rangle$. The value is written as string (verbatim).

The $\langle comma-separated-list \rangle$ is processed via TikZ's `\foreach` command, that means you can use ... expressions to provide number (or character) ranges.

level	my new col	
1	A	<pre>\pgfplotstableset{ create on use/my new col/.style={ create col/set list={A,B,C,4,50,55,...,100}}, columns/my new col/.style={string type} } \pgfplotstabletypeset[columns={level,my new col},]{pgfplotstable.example1.dat}</pre>
2	B	
3	C	
4	4	
5	50	
6	55	
7	60	
8	65	
9	70	
10	75	

The new column will be padded or truncated to the required number of rows. If the list does not contain enough elements, empty cells will be produced.

`/pgfplots/table/create col/copy= $\langle column name \rangle$`

A style for use in column creation context which simply copies the existing column $\langle column name \rangle$.

level	Copy of level
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10

```

\pgfplotstableset{
  create on use/new/.style={create col/copy={level}}
}

\pgfplotstabletypeset[
  columns={level,new},
  columns/new/.style={column name=Copy of level}
]{pgfplotstable.example1.dat}

```

`/pgfplots/table/create col/copy column from table={\file name or \macro}}{\column name}`

A style for use in column creation context which creates a new column consisting of the entries in `{\column name}` of the provided table. The argument may be either a file name or an already loaded table (i.e. a `\macro` as returned by `\pgfplotstableread`).

You can use this style, possibly combined with `\pgfplotstablenew`, to merge one common sort of column from different tables into one large table.

The cell values are written as string (verbatim).

The new column will be padded or truncated to the required number of rows. If the list does not contain enough elements, empty cells will be produced.

4.3.2 Mathematical Operations

`/pgf/fpu={\true,\false}`

Before we start to describe the column generation methods, one word about the math library. The core is always the PGF math engine written by Mark Wibrow and Till Tantau. However, this engine has been written to produce graphics and is not suitable for scientific computing.

I added a high-precision floating point library to PGF which will be part of releases newer than PGF 2.00. It offers the full range of IEEE double precision computing in TeX. This FPU is also part of PGF-PLOTSTABLE, and it is activated by default for `create col/expr` and all other predefined mathematical methods.

The FPU won't be active for newly defined numerical styles. If you want to add own routines or styles, you will need to use

```
\pgfkeys{/pgf/fpu=true}
```

in order to activate the extended precision. The standard math parser is limited to fixed point numbers in the range ± 16384.00000 .

`/pgfplots/table/create col/expr={\math expression}`

A style for use in `\pgfplotstablecreatecol` which uses `{\math expression}` to assign contents for the new column.

level	2·level
1	2
2	4
3	6
4	8
5	10
6	12
7	14
8	16
9	18
10	20

```

\pgfplotstableset{
  create on use/new/.style={
    create col/expr={\thisrow{level}*2}}
}

\pgfplotstabletypeset[
  columns={level,new},
  columns/new/.style={column name=$2\cdot $level}
]{pgfplotstable.example1.dat}

```

The macros `\thisrow{\column name}` and `\nextrow{\column name}` can be used to use values of the existing table.

Please see `\pgfplotstablecreatecol` for more information.

Accumulated columns: The `expr` style initialises `\pgfmathaccuma` to 0 before its first column. Whenever it computes a new column value, it redefines `\pgfmathaccuma` to be the result. That means you can use `\pgfmathaccuma` inside of $\langle\mathit{expression}\rangle$ to accumulate columns. See `create col/expr accum` for more details.

About the precision and number range: Starting with version 1.2, `expr` uses a floating point unit. The FPU provides the full data range of scientific computing with a relative precision between 10^{-4} and 10^{-6} . The `/pgf/fpu` key provides some more details.

Accepted operations: The math parser of PGF, combined with the FPU, provides the following function and operators:

`+`, `-`, `*`, `/`, `abs`, `round`, `floor`, `mod`, `<`, `>`, `max`, `min`, `sin`, `cos`, `tan`, `deg` (conversion from radians to degrees), `rad` (conversion from degrees to radians), `atan`, `asin`, `acos`, `cot`, `sec`, `cosec`, `exp`, `ln`, `sqrt`, the constant `pi` and `e`, `^` (power operation), `factorial`⁵, `rand` (random between -1 and 1), `rnd` (random between 0 and 1), number format conversions `hex`, `Hex`, `oct`, `bin` and some more. The math parser has been written by Mark Wibrow and Till Tantau [1], the FPU routines have been developed as part of PGFPLOTS. The documentation for both parts can be found in [1]. **Attention:** Trigonometric functions work with degrees, not with radians!

`/pgfplots/table/create col/expr accum= $\langle\mathit{expression}\rangle$ { $\langle\mathit{accum initial}\rangle$ }`

A variant of `create col/expr` which also allows to define the initial value of `\pgfmathaccuma`. The case $\langle\mathit{accum initial}\rangle=0$ is equivalent to `expr= $\langle\mathit{expression}\rangle$` .

level	\sum level	\prod level
1	1	99
2	3	97
3	6	94
4	10	90
5	15	85
6	21	79
7	28	72
8	36	64
9	45	55
10	55	45

```
\pgfplotstableset{
  create on use/new/.style={
    create col/expr={\pgfmathaccuma + \thisrow{level}},
  }
  create on use/new2/.style={
    create col/expr accum={\pgfmathaccuma - \thisrow{level}}{100}
  }
}

\pgfplotstabletypeset[
  columns={level,new,new2},
  columns/new/.style={column name=\sum$level},
  columns/new2/.style={column name=\prod$level}
]{pgfplotstable.example1.dat}
```

The example creates two columns: the `new` column is just the sum of each value in the $\langle\mathit{level}\rangle$ column (it employs the default `\pgfmathaccuma=0`). The `new2` column initialises `\pgfmathaccuma=100` and then successively subtracts the value of $\langle\mathit{level}\rangle$.

`/pgfplots/table/create col/quotient= $\langle\mathit{column name}\rangle$`

A style for use in `\pgfplotstablecreatecol` which computes the quotient $c_i := m_{i-1}/m_i$ for every entry $i = 1, \dots, (n-1)$ in the column identified with $\langle\mathit{column name}\rangle$. The first value c_0 is kept empty.

⁵Starting with PGF versions newer than 2.00, you can use the postfix operator `!` instead of `factorial`.

error1	error2	quot1	quot2
$2.50 \cdot 10^{-1}$	$7.58 \cdot 10^{-1}$		
$6.25 \cdot 10^{-2}$	$5.00 \cdot 10^{-1}$	4	1.52
$1.56 \cdot 10^{-2}$	$2.87 \cdot 10^{-1}$	4	1.74
$3.91 \cdot 10^{-3}$	$1.44 \cdot 10^{-1}$	4	2
$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	4	3.25
$2.44 \cdot 10^{-4}$	$1.70 \cdot 10^{-2}$	4	2.6
$6.10 \cdot 10^{-5}$	$8.20 \cdot 10^{-3}$	4	2.07
$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	4	2.1
$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	4	2
$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	4	2

```
% requires \usepackage{array}
\pgfplotstableset{% configuration, for example, in preamble:
  create on use/quot1/.style={create col/quotient=error1},
  create on use/quot2/.style={create col/quotient=error2},
  columns={error1,error2,quot1,quot2},
  %
  % display styles:
  columns/error1/.style={sci,sci zerofill},
  columns/error2/.style={sci,sci zerofill},
  columns/quot1/.style={dec sep align},
  columns/quot2/.style={dec sep align}
}

\pgfplotstabletypeset{pgfplotstable.example1.dat}
```

This style employs methods of the floating point unit, that means it works with a relative precision of about 10^{-7} (7 significant digits in the mantisse).

`/pgfplots/table/create col/iquotient={⟨column name⟩}`

Like `create col/quotient`, but the quotient is inverse.

`/pgfplots/table/create col/dyadic refinement rate={⟨column name⟩}`

A style for use in `\pgfplotstablecreatecol` which computes the convergence rate α of the data in column `{⟨column name⟩}`. The contents of `{⟨column name⟩}` is assumed to be something like $e_i(h_i) = O(h_i^\alpha)$. Assuming a dyadic refinement relation from one row to the next, $h_i = h_{i-1}/2$, we have $h_{i-1}^\alpha / (h_{i-1}/2)^\alpha = 2^\alpha$, so we get α using

$$c_i := \log_2 \left(\frac{e_{i-1}}{e_i} \right).$$

The first value c_0 is kept empty.

error1	error2	rate1	rate2
$2.50 \cdot 10^{-1}$	$7.58 \cdot 10^{-1}$		
$6.25 \cdot 10^{-2}$	$5.00 \cdot 10^{-1}$	2	0.6
$1.56 \cdot 10^{-2}$	$2.87 \cdot 10^{-1}$	2	0.8
$3.91 \cdot 10^{-3}$	$1.44 \cdot 10^{-1}$	2	1
$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	2	1.7
$2.44 \cdot 10^{-4}$	$1.70 \cdot 10^{-2}$	2	1.38
$6.10 \cdot 10^{-5}$	$8.20 \cdot 10^{-3}$	2	1.05
$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	2	1.07
$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	2	1
$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	2	1

```
% requires \usepackage{array}
\pgfplotstabletypeset[% here, configuration options apply only to this single statement:
  create on use/rate1/.style={create col/dyadic refinement rate={error1}},
  create on use/rate2/.style={create col/dyadic refinement rate={error2}},
  columns={error1,error2,rate1,rate2},
  columns/error1/.style={sci,sci zerofill},
  columns/error2/.style={sci,sci zerofill},
  columns/rate1/.style={dec sep align},
  columns/rate2/.style={dec sep align}
]{pgfplotstable.example1.dat}
```

This style employs methods of the floating point unit, that means it works with a relative precision of about 10^{-6} (6 significant digits in the mantisse).

`/pgfplots/table/create col/dyadic refinement rate={\langle column name \rangle}`

As `create col/dyadic refinement rate`, but the quotient is inverse.

`/pgfplots/table/create col/gradient={\langle col x \rangle}{\langle col y \rangle}`

`/pgfplots/table/create col/gradient loglog={\langle col x \rangle}{\langle col y \rangle}`

`/pgfplots/table/create col/gradient semilogx={\langle col x \rangle}{\langle col y \rangle}`

`/pgfplots/table/create col/gradient semilogy={\langle col x \rangle}{\langle col y \rangle}`

A style for `\pgfplotstablecreatecol` which computes piecewise gradients $(y_{i+1} - y_i)/(x_{i+1} - x_i)$ for each row. The y values are taken out of column `{\langle col y \rangle}` and the x values are taken from `{\langle col y \rangle}`.

The logarithmic variants apply the natural logarithm, $\log(\cdot)$, to its argument before starting to compute differences. More precisely, the `loglog` variant applies the logarithm to both, x and y , the `semilogx` variant applies the logarithm only to x and the `semilogy` variant applies the logarithm only to y .

dof	error1	error2	slopes1	slopes2
4	$2.50 \cdot 10^{-1}$	$7.58 \cdot 10^{-1}$		
16	$6.25 \cdot 10^{-2}$	$5.00 \cdot 10^{-1}$	-1	-0.3
64	$1.56 \cdot 10^{-2}$	$2.87 \cdot 10^{-1}$	-1	-0.4
256	$3.91 \cdot 10^{-3}$	$1.44 \cdot 10^{-1}$	-1	-0.5
1,024	$9.77 \cdot 10^{-4}$	$4.42 \cdot 10^{-2}$	-1	-0.85
4,096	$2.44 \cdot 10^{-4}$	$1.70 \cdot 10^{-2}$	-1	-0.69
16,384	$6.10 \cdot 10^{-5}$	$8.20 \cdot 10^{-3}$	-1	-0.52
65,536	$1.53 \cdot 10^{-5}$	$3.91 \cdot 10^{-3}$	-1	-0.54
262,144	$3.81 \cdot 10^{-6}$	$1.95 \cdot 10^{-3}$	-1	-0.5
1,048,576	$9.54 \cdot 10^{-7}$	$9.77 \cdot 10^{-4}$	-1	-0.5

```
% requires \usepackage{array}
\pgfplotstableset{% configuration, for example in preamble:
  create on use/slopes1/.style={create col/gradient loglog={dof}{error1}},
  create on use/slopes2/.style={create col/gradient loglog={dof}{error2}},
  columns={dof,error1,error2,slopes1,slopes2},
  % display styles:
  columns/dof/.style={int detect},
  columns/error1/.style={sci,sci zerofill},
  columns/error2/.style={sci,sci zerofill},
  columns/slopes1/.style={dec sep align},
  columns/slopes2/.style={dec sep align}
}
\pgfplotstabletypeset{pgfplotstable.example1.dat}
```

level	error1	slopes1
1	2.50_{-1}	
2	6.25_{-2}	-1.39
3	1.56_{-2}	-1.39
4	3.91_{-3}	-1.39
5	9.77_{-4}	-1.39
6	2.44_{-4}	-1.39
7	6.10_{-5}	-1.39
8	1.53_{-5}	-1.39
9	3.81_{-6}	-1.39
10	9.54_{-7}	-1.39


```
% requires \usepackage{array}
\pgfplotstableset{% configuration, for example in preamble:
  create on use/slopes1/.style={create col/gradient semilogy={level}{error1}},
  columns={level,error1,slopes1},
  % display styles:
  columns/level/.style={int detect},
  columns/error1/.style={sci,sci zerofill,sci subscript},
  columns/slopes1/.style={dec sep align}
}
\pgfplotstabletypeset{pgfplotstable.example1.dat}
```

This style employs methods of the floating point unit, that means it works with a relative precision of about 10^{-6} (6 significant digits in the mantisse).

`/pgfplots/table/create col/function graph cut y={\cut value}{\common options}{\one key-value set for each plot}`

A specialized style for use in `create on use` statements which computes cuts of (one or more) discrete plots $y(x_1), \dots, y(x_N)$ with a fixed $\{\text{\cut value}\}$. The x_i are written into the table's cells.

In a cost–accuracy plot, this feature allows to extract the cost for fixed accuracy. The dual feature with `cut x` allows to compute the accuracy for fixed cost.



```

\pgfplotstablenew[
  create on use/cut/.style={create col/function graph cut y=
    {2.5e-4}% search for fixed L2 = 2.5e-4
    {x=Basis,y=L2,ymode=log,xmode=log}% double log, each function is L2(Basis)
% now, provide each single function f_i(Basis):
{table=plotdata/newexperiment1.dat},{table=plotdata/newexperiment2.dat}}
  },
  columns={cut}]
{2}
\table
\pgfplotstabletypeset{\table}

\begin{tikzpicture}
\begin{loglogaxis}
  \addplot table[x=Basis,y=L2] {plotdata/newexperiment1.dat};
  \addplot table[x=Basis,y=L2] {plotdata/newexperiment2.dat};
  \draw[blue!30!white] (axis cs:1,2.5e-4) -- (axis cs:1e5,2.5e-4);
  \node[pin=-90:{$x=53.66$}] at (axis cs:53.66,2.5e-4) {};
  \node[pin=45:{$x=601.83$}] at (axis cs:601.83,2.5e-4) {};
\end{loglogaxis}
\end{tikzpicture}

```

In the example above, we are searching for x_1 and x_2 such that $f_1(x_1) = 2.5 \cdot 10^{-4}$ and $f_2(x_2) = 2.5 \cdot 10^{-4}$. On the left is the automatically computed result. On the right is a problem illustration with proper annotation. The $\{\text{\cut value}\}$ is set to $2.5e-4$. The $\{\text{\common options}\}$ contain the problem setup; in our case logarithmic scales and column names. The third argument is a comma-separated-list. Each element i is a set of keys describing how to get $f_i(\cdot)$.

During both, $\{\text{\common options}\}$ and the key sets, the following keys can be used:

- `table`: either a file name or an already loaded table where to get the data points,
- `x`: the column name of the x axis,
- `y`: the column name of the y axis.

The keys `xmode` and `ymode` can take either `log` or `linear`. All mentioned keys have the common key path

`/pgfplots/table/create col/function graph cut/.`

`/pgfplots/table/create col/function graph cut x={\cut value}{\common options}{\one key-value set for each plot}`

As above, just with x and y exchanged.

5 Miscellaneous

5.1 Writing (Modified) Tables To Disk

`/pgfplots/table/outfile={⟨file name⟩}` (initially empty)

Writes the completely processed table as T_EX file to {⟨file name⟩}. This key is described in all detail on page 12.

`\pgfplotstablesave[⟨options⟩]{⟨macro or input file name⟩}{⟨output file name⟩}`

This command takes a table and writes it to a new data file (without performing any typesetting).

If the first argument is a file name, that file is loaded first.

This command simply invokes `\pgfplotstabletypeset` with cleared output parameters. That means any of the column creation methods apply here as well, including any postprocessing steps (without the final typesetting).

`\pgfplotstablesave` uses the keys `reset styles` and `disable rowcol styles` to clear any typesetting related options. Furthermore, it sets `string type` to allow verbatim output.

```
\pgfplotstablesave[
  create on use/postproci/.style={create col/dyadic refinement rate=error1},
  columns={dof,error1,postproci}
]
{pgfplotstable.example1.dat}
{pgfplotstable.example1.out.dat}
```

Now, `pgfplotstable.example1.out.dat` is

```
dof      error1  postproci
4        2.50000000e-01  {}
16       6.25000000e-02  1.99998
64       1.56250000e-02  1.99998
256      3.90625000e-03  1.99998
1024     9.76562500e-04  1.99998
4096     2.44140625e-04  1.99998
16384    6.10351562e-05  1.99998
65536    1.52587891e-05  1.99998
262144   3.81469727e-06  1.99998
1048576  9.53674316e-07   1.99998
```

You can use the `col sep` key inside of `⟨options⟩` to define a column separator for the output file. In case you need a different input column separator, use `in col sep` instead of `col sep`.

Remarks

- Empty cells will be filled with `{}` if `col sep=space`. Use the `empty cells with style` to change that.
- Use `disable rowcol styles=false` inside of `⟨options⟩` if you need to change column/row based styles.

5.2 Miscellaneous Keys

`/pgfplots/table/disable rowcol styles=true|false` (initially false)

Set this to true if `\pgfplotstabletypeset` shall *not* set any styles which apply only to specific columns or only to specific rows.

This disables the styles

- `columns/⟨column name⟩`,
- `display columns/⟨column index⟩`,
- `every col no ⟨column index⟩`,
- `every row no ⟨row index⟩`.

`/pgfplots/table/reset styles` (no value)

Resets all table typesetting styles which do not explicitly depend on column or row names and indices. The affected styles are

- `every table`,
- `every even row`, `every odd row`, `every even column`, `every odd column`,
- `every first column`, `every last column`, `every first row`, `every last row`,
- `every head row`.

In case you want to reset all, you should also consider the key `disable rowcol styles`.

5.3 Plain `TeX` and `ConTeXt` support

The table code generator is initialised to produce `LATeX` `tabular` environments. However, it only relies on `&` being the column separator and `\` the row terminator. The `column type` feature is more or less specific to `tabular`, but you can disable it completely. Replace `begin table` and `end table` with appropriate `TeX`- or `ConTeXt` commands to change it. If you have useful default styles (or bug reports), let me know.

Index

— Symbols —	
1000 sep key	17
— A —	
after row key	10
alias key	6
assign cell content key	20
assign cell content as number key	20
assign column name key	7
assume math mode key	19
— B —	
before row key	10
begin table key	11
— C —	
clear infinite key	22
col sep key	5
column type key	7
columns key	5f.
copy key	30
copy column from table key	31
create on use key	29
— D —	
date type key	20
\day	21
dcolumn key	9
debug key	13
dec sep key	16
dec sep align key	8
disable rowcol styles key	36
display columns key	7
divide by key	22
dyadic refinement rate key	33
— E —	
empty cells with key	26
end table key	12
every col no $\langle index \rangle$ key	7
every even column key	9
every even row key	10
every first column key	9
every first row key	11
every head row key	11
every last column key	9
every last row key	11
every odd column key	10
every odd row key	11
every row no $\langle index \rangle$ key	11
every table key	11
expr key	31
expr accum key	32
— F —	
fixed key	14
fixed zerofill key	15
Floating Point Unit	32
font key	11
force remake key	13
fpu key	31
function graph cut x key	35
function graph cut y key	35
— G —	
gradient key	34
gradient loglog key	34
gradient semilogx key	34
gradient semilogy key	34
— H —	
header key	5
— I —	
idyadic refinement rate key	34
include outfiles key	12
int detect key	16
int trunc key	16
iquotient key	33
— M —	
min exponent for 1000 sep key	17
\month	21
\monthname	21
\monthshortname	21
multicolumn names key	8
multiply -1 key	23
multiply with key	22
— N —	
\newcolumn type	13
— O —	
outfile key	12, 36
— P —	
/pgf/	
fpu	31
number format/	
1000 sep	17
assume math mode	19
dec sep	16
fixed	14
fixed zerofill	15
int detect	16
int trunc	16
min exponent for 1000 sep	17
precision	16
print sign	18
sci	15
sci 10 ^e	18
sci 10e	18
sci E	19
sci e	18
sci subscript	19
sci superscript	19
sci zerofill	15
set decimal separator	16
set thousands separator	16
showpos	18
skip 0.	18
std	15

use comma	18
use period	17
zerofill	15
\pgfmathprintnumber	14
\pgfmathprintnumberto	14
\pgfplotstablecol	10
\pgfplotstablecols	10
\pgfplotstablecreatecol	27
\pgfplotstablegetrowsof	4
\pgfplotstableread	26
\pgfplotstableread	4
\pgfplotstablerow	10
\pgfplotstablerows	10
\pgfplotstablesave	36
\pgfplotstableset	2
\pgfplotstabletypeset	3
\pgfplotstabletypesetfile	4
\pgfplotstablevertcat	27
postproc cell content key	25
Precision	31f.
precision key	16
preproc cell content key	21
print sign key	18

— Q —

quotient key	32
--------------	----

— R —

reset styles key	36
row predicate key	23

— S —

sci key	15
sci 10 ^e key	18
sci 10e key	18
sci E key	19
sci e key	18
sci sep align key	9
sci subscript key	19
sci superscript key	19
sci zerofill key	15
select equal part entry of key	24
set key	30
set content key	26
set decimal separator key	16
set list key	30
set thousands separator key	16
showpos key	18
skip 0. key	18
skip coltypes key	13
skip rows between index key	24
sqrt key	22
std key	15
string replace key	22
string type key	20

— T —

table/	
after row	10
alias	6
assign cell content	20
assign cell content as number	20
assign column name	7
before row	10

begin table	11
clear infinite	22
col sep	5
column type	7
columns	5f.
create col/	
copy	30
copy column from table	31
dyadic refinement rate	33
expr	31
expr accum	32
function graph cut x	35
function graph cut y	35
gradient	34
gradient loglog	34
gradient semilogx	34
gradient semilogy	34
idyadic refinement rate	34
iquotient	33
quotient	32
set	30
set list	30
create on use	29
date type	20
dcolumn	9
debug	13
dec sep align	8
disable rowcol styles	36
display columns	7
divide by	22
empty cells with	26
end table	12
every col no <i><index></i>	7
every even column	9
every even row	10
every first column	9
every first row	11
every head row	11
every last column	9
every last row	11
every odd column	10
every odd row	11
every row no <i><index></i>	11
every table	11
font	11
force remake	13
header	5
include outfiles	12
multicolumn names	8
multiply -1	23
multiply with	22
outfile	12, 36
postproc cell content	25
preproc cell content	21
reset styles	36
row predicate	23
sci sep align	9
select equal part entry of	24
set content	26
skip coltypes	13
skip rows between index	24
sqrt	22
string replace	22

string type.....	20
TeX comment.....	13
typeset	13
typeset cell.....	11
write to macro	13
TeX comment key	13
typeset key.....	13
typeset cell key	11
— U —	
use comma key	18
use period key	17
— W —	
\weekday.....	21
\weekdayname	21
\weekdayshortname	21
write to macro key.....	13
— Y —	
\year	21
— Z —	
zerofill key.....	15

References

- [1] T. Tantau. TikZ and PGF manual. <http://sourceforge.net/projects/pgf>. *v.* ≥ 2.00 .